

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>Interior Convenience/Driver Retention Package</b>		
INTERIOR CONVENIENCE PACKAGE		
<b>Vehicle Configuration</b>		
M2 106 CONVENTIONAL CHASSIS	5,759	3,503
2016 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK		
STRAIGHT TRUCK PROVISION		
LH PRIMARY STEERING LOCATION		
<b>General Service</b>		
TRUCK CONFIGURATION		
DOMICILED, CANADA (OTHER THAN QUEBEC)		
PICKUP AND DELIVERY/SHORT HAUL SERVICE		
GENERAL FREIGHT BUSINESS SEGMENT		
GENERAL FREIGHT COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
MEDIUM TRUCK WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 21000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs		
EXPECTED GROSS COMBINATION WEIGHT : 0.0 lbs		
<b>Truck Service</b>		
DRY VAN BODY		
EXPECTED TRUCK BODY LENGTH : 22.0 ft		

Description	Weight Front	Weight Rear
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
<b>Engine</b>		
CUM ISB 6.7-260 260 HP @ 2300 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM		
<b>Electronic Parameters</b>		
65 MPH ROAD SPEED LIMIT		
<b>Engine Equipment</b>		
2015 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG14		
NO 2008 CARB EMISSION CERTIFICATION		
STANDARD OIL PAN		
ENGINE MOUNTED OIL CHECK AND FILL		
ONE PIECE VALVE COVER		
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER		
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE		
(2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES		
BATTERY BOX FRAME MOUNTED		
STANDARD BATTERY JUMPERS		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH	20	

Description	Weight Front	Weight Rear
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH STANDARD HORIZONTAL TAILPIPE		
13 GALLON DIESEL EXHAUST FLUID TANK	35	10
100 PERCENT DIESEL EXHAUST FLUID FILL		
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
HORTON HT650 FRONTAL AIR ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
FULL FLOW OIL FILTER		
950 SQUARE INCH ALUMINUM RADIATOR		
ANTIFREEZE TO -60F, OAT (NITRITE & SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
RADIATOR DRAIN VALVE		
LOWER RADIATOR GUARD		
PHILLIPS-TEMRO 750 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
CUSTOM STARTER		

**Transmission**

ALLISON 2500 HS AUTOMATIC TRANSMISSION, NO PTO PROVISION

**Transmission Equipment**

Description	Weight Front	Weight Rear
ALLISON VOCATIONAL PACKAGE 354 - AVAILABLE ON 1000/2000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, EVS, HS, MH, PTS AND SPS		
ALLISON VOCATIONAL RATING FOR HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, 6 FORWARD GEARS WITH MANUAL SELECTION FOR 3, 2 AND 1, AVAILABLE FOR 1000/2000 PRODUCT FAMILIES ONLY		
NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED		
MARKER LAMP CONNECTION FOR BODY BUILDERS		
ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
DASH MOUNTED T-HANDLE CABLE SHIFT CONTROL WITHOUT PARK BRAKE POSITION		
TRANSMISSION PROGNOSTICS - DISABLED (N/A) 2013, FOR USE IN 1000/2000 ONLY		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

**Front Axle and Equipment**

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE		
MERITOR 15X4 Q+ CAM FRONT BRAKES		
NON-ASBESTOS FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
SKF SCOTSEAL PLUS XL FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW THP-60 POWER STEERING		
POWER STEERING PUMP		

Description	Weight Front	Weight Rear
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
12,000# DUAL TAPERLEAF FRONT SUSPENSION	42	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS	30	
<b>Rear Axle and Equipment</b>		
DETROIT DA-RS-23.0-4 23,000# R-SERIES SINGLE REAR AXLE		30
6.14 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	40	40
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		
SKF SCOTSEAL PLUS XL REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>Rear Suspension</b>		
AIRLINER 23,000# REAR SUSPENSION WITH CHAIN CLEARANCE		180
AIRLINER HIGH POSITION RIDE HEIGHT		
STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
IGNITION CONTROLLED ELECTRIC DUMP SWITCH FOR AIR SUSPENSION WITH AUTOFILL OVERRIDE VALVE		
REAR AIR SUSPENSION DUMP VALVE WITH AUTOFILL FOR IGNITION OFF AND >5 MPH, INCLUDE OVERRIDE CONTROL AND BUZZER ON DUMP VALVE SWITCH		

Description	Weight Front	Weight Rear
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - ONE AXLE (AIR RIDE SUSPENSION)		
<b>Brake System</b>		
AIR BRAKE PACKAGE		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED UNDER HOOD		
STEEL AIR BRAKE RESERVOIRS		
BW DV-2 AUTO DRAIN VALVE WITH HEATER TO WET TANK; DRAIN VALVE CABLES ON ALL OTHER TANKS		
<b>Trailer Connections</b>		
UPGRADED CHASSIS MULTIPLEXING UNIT		
UPGRADED BULKHEAD MULTIPLEXING UNIT		
<b>Wheelbase &amp; Frame</b>		
6400MM (252 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	390	150
3050MM (120 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 111 INCH TO 120 INCH	-70	310
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 186.45 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 183.45 in		
CALC'D FRAME LENGTH - OVERALL : 401.39		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 186.45 in		
CALCULATED FRAME SPACE LH SIDE : 93.27 in		

Description	Weight Front	Weight Rear
CALCULATED FRAME SPACE RH SIDE : 190.11 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REAR MOST CROSSMEMBER		
HEAVY DUTY SUSPENSION CROSSMEMBER		30
<b>Chassis Equipment</b>		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED	15	
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
LEVEL FRAME RAILS (+/- 1%) WHEN CHASSIS IS LOADED TO FRONT AND REAR SUSPENSION RATINGS		
<b>Fuel Tanks</b>		
100 GALLON/378 LITER RECTANGULAR ALUMINUM FUEL TANK - LH	80	10
RECTANGULAR FUEL TANK(S)		
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
FUEL TANK(S) FORWARD		
POLISHED STAINLESS STEEL STEP FINISH		
FUEL TANK CAP(S)		
ALLIANCE FUEL FILTER/WATER SEPARATOR WITH HEATED BOWL AND PRIMER PUMP		
EQUIFLO INBOARD FUEL SYSTEM		
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
<b>Tires</b>		
MICHELIN XZA3+ 11R22.5 14 PLY RADIAL FRONT TIRES	12	
MICHELIN XDE M/S 11R22.5 14 PLY RADIAL REAR TIRES		28
<b>Hubs</b>		

Description	Weight Front	Weight Rear
CONMET PRESET PLUS IRON FRONT HUBS		
CONMET PRESET PLUS ALUMINUM REAR HUBS		-30
<b>Wheels</b>		
ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT 5.79 INSET ALUMINUM DISC FRONT WHEELS	-50	
ALCOA LVL ONE 88367X ALUMINUM OUTSIDE, ACCURIDE 29637 STEEL INSIDE; 22.5X8.25 10-HUB PILOT DISC REAR WHEELS		-28
POLISHED FRONT WHEELS; OUTSIDE ONLY		
POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
FRONT WHEEL MOUNTING NUTS		
REAR WHEEL MOUNTING NUTS		
NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		
<b>Cab Exterior</b>		
106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
AIR CAB MOUNTS		
NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
LH AND RH GRAB HANDLES		
HOOD MOUNTED CHROMED PLASTIC GRILLE		
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
HOOD LINER INSULATION WITH SINGLE FIREWALL INSULATION		
SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK	4	
DUAL ELECTRIC HORNS		
SINGLE HORN SHIELD		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS		
REAR LICENSE PLATE MOUNT END OF FRAME		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS - LOW BEAM ONLY		
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS		
STANDARD FRONT TURN SIGNAL LAMPS		
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS		



Description	Weight Front	Weight Rear
DOOR MOUNTED MIRRORS 102 INCH EQUIPMENT WIDTH LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS STANDARD SIDE/REAR REFLECTORS COMPOSITE EXTERIOR SUN VISOR 63X14 INCH TINTED REAR WINDOW TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS RH AND LH ELECTRIC POWERED WINDOWS TINTED WINDSHIELD 2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, FRAME MOUNTED	10	4

### Cab Interior

OPAL GRAY VINYL INTERIOR MOLDED DOOR PANEL WITH UPPER VINYL INSERTS MOLDED DOOR PANEL WITH UPPER VINYL INSERTS BLACK MATS WITH SINGLE INSULATION FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS AND ADDITIONAL CENTER COMPARTMENT WITHOUT NETTING IN DASH STORAGE BIN CENTER STORAGE CONSOLE MOUNTED ON BACKWALL (2) CUP HOLDERS LH AND RH DASH GRAY/CHARCOAL FLAT DASH SMART SWITCH EXPANSION MODULE 2-1/2 LB. FIRE EXTINGUISHER FIRST AID KIT HEATER, DEFROSTER AND AIR CONDITIONER STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH STANDARD HEATER PLUMBING DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR BINARY CONTROL, R-134A	20	5 2
--	----	--------

Description	Weight Front	Weight Rear
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOMED DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF		
LH AND RH ELECTRIC DOOR LOCKS		
(1) 12 VOLT POWER SUPPLY IN DASH		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30	
BASIC HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	25	10
INBOARD DRIVER SEAT ARMREST, NO PASSENGER SEAT ARMREST	2	
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
GRAY MORDURA CLOTH DRIVER SEAT COVER		
GRAY MORDURA CLOTH PASSENGER SEAT COVER		
3 POINT FIXED D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10	
4-SPOKE 18 INCH (450MM) STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

### Instruments & Controls

WOODGRAIN DRIVER INSTRUMENT PANEL		
WOODGRAIN CENTER INSTRUMENT PANEL		
BLACK GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
97 DB BACKUP ALARM		3
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		

Description	Weight Front	Weight Rear
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED		
DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH		
2 INCH ELECTRIC FUEL GAUGE		
PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
NO LANE DEPARTURE WARNING SYSTEM		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, USB, FRONT AND REAR AUXILIARY INPUTS AND J1939	10	
DASH MOUNTED RADIO		
(2) RADIO SPEAKERS IN CAB		
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
RADIO WIRING WITH POWER CUTOFF WHEN VEHICLE IN REVERSE GEAR		
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
IDLE LIMITER, ELECTRONIC ENGINE		
ONE ON/OFF ROCKER SWITCH IN THE DASH WITH INDICATOR LIGHT AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT		
PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY PROGRAMMED TO SLOWEST SPEED WITH PARK BRAKE SET		
MARKER LIGHT/HEADLIGHT SWITCH WITH SEPARATE INTERRUPTER FOR CLEARANCE LIGHTS		
ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		

Description	Weight Front	Weight Rear
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE		
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS		
NO MISCELLANEOUS GAUGES		

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: N0225EA WHITE ELITE SS  
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT  
 NO FUEL TANK CABINET PAINT  
 POWDER WHITE (N0006EA) REAR  
 WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
 SUNVISOR PAINTED SAME AS CAB COLOR A  
 STANDARD E COAT/UNDERCOATING

**Certification / Compliance**

CANADA CMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

**T O T A L V E H I C L E S U M M A R Y**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	6504 lbs	4246 lbs	10750 lbs
Total Weight <sup>+</sup>	6504 lbs	4246 lbs	10750 lbs

**Extended Warranty**

TOWING EXTENDED/ROADSIDE SERVICE WARRANTY, 1 YEAR/UNLIMITED MILES/KM, \$550 CAP

**Prepared by:**  
CURRIE TRUCK CENTRE  
2 Currie Drive  
Midhurst, ON L0L 1X0  
Phone: 705 734-1953

(+) Weights shown are estimates only.  
If weight is critical, contact Customer Application Engineering.