

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>Interior Convenience/Driver Retention Package</b>		
INTERIOR CONVENIENCE PACKAGE		
<b>Vehicle Configuration</b>		
114SD CONVENTIONAL CHASSIS	7,934	6,576
2017 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK	480	-480
STRAIGHT TRUCK PROVISION		
LH PRIMARY STEERING LOCATION		
<b>General Service</b>		
TRUCK CONFIGURATION		
DOMICILED, CANADA (OTHER THAN QUEBEC)		
PICKUP AND DELIVERY/SHORT HAUL SERVICE		
PETROLEUM BUSINESS SEGMENT		
LIQUID BULK COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
FREIGHTLINER LEVEL II WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 60000.0 lbs		
EXPECTED GROSS COMBINATION WEIGHT : 0.0 lbs		
<b>Truck Service</b>		
TANK BODY		
EXPECTED TRUCK BODY LENGTH : 0.0 ft		

Description	Weight Front	Weight Rear
BRAKING-EXPECTED CAB TO BODY CLEARANCE : 15.0 in		
<b>Engine</b>		
DETROIT DD13 12.8L 410 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM		
<b>Electronic Parameters</b>		
65 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT, WITH AUTO RESUME AFTER SHIFT		
<b>Engine Equipment</b>		
2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR) NO 2013 ENGINE ESCALATOR STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	10	
(3) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADED STUD BATTERIES BATTERY BOX FRAME MOUNTED STANDARD BATTERY JUMPERS SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN NON-POLISHED BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT EATON SOLO ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH TORQUE LIMITING CLUTCH BRAKE ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING	8	

Description	Weight Front	Weight Rear
HYDRAULIC CLUTCH CONTROL		
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
JACOBS COMPRESSION BRAKE		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND DASH MOUNTED SINGLE REGENERATION REQUEST/INHIBIT SWITCH		
12 FOOT 00 INCH (144 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
STANDARD CURVE BRIGHT UPPER STACK(S)		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
6 GALLON DIESEL EXHAUST FLUID TANK	-35	-10
100 PERCENT DIESEL EXHAUST FLUID FILL		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD		
BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
FULL FLOW OIL FILTER		
1500 SQUARE INCH ALUMINUM RADIATOR		
ANTIFREEZE TO -60F, OAT (NITRITE & SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE		

Description	Weight Front	Weight Rear
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		

### Transmission

EATON FULLER FRO-16210C TRANSMISSION	60	20
--------------------------------------	----	----

### Transmission Equipment

NO TCU-LBSS_VAC		
TCU DRIVER SW INPUTS NOT SUPPORTED		
VEHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT END OF FRAME		
ALUMINUM CLUTCH HOUSING		
(2) CUSTOMER INSTALLED MUNCIE PTO'S: TG6 AND TG8 SERIES		
PTO MOUNTING, RH AND BOTTOM OF MAIN TRANSMISSION		
MAGNETIC TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN, ENGINE DRAIN; PAINT DRAIN PLUGS YELLOW		
PAINTED SHIFT LEVER, SOLID LINKAGE		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK	-30	
SYNTHETIC TRANSMISSION LUBE		

### Front Axle and Equipment

DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	210	
MERITOR 16.5X6 Q+ CAST SPIDER HEAVY DUTY CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
SKF SCOTSEAL PLUS XL FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
WABCO LONGSTROKE FRONT BRAKE CHAMBERS		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		

Description	Weight Front	Weight Rear
STANDARD KING PIN BUSHINGS		
TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	130	
POWER STEERING PUMP		
4 QUART POWER STEERING RESERVOIR		
OIL/AIR POWER STEERING COOLER		
SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
20,000# TAPERLEAF FRONT SUSPENSION	200	
GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		
MT-40-14XP 40,000# R-SERIES TANDEM REAR AXLE		-30
3.55 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING		40
RPL25SD MERITOR MAIN DRIVELINE	60	60
RPL20 MERITOR INTERAXLE DRIVELINE		
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		30
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE		
BLINKING LAMP WITH EACH INTERAXLE LOCK SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF		
BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH		
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
SKF SCOTSEAL PLUS XL REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		

Description	Weight Front	Weight Rear
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
SYNTHETIC 75W-90 REAR AXLE LUBE		
STANDARD REAR AXLE BREATHER(S)		
<b>Rear Suspension</b>		
AIRLINER 46,000# REAR SUSPENSION		420
AIRLINER HIGH POSITION RIDE HEIGHT		
RESTRAINED AXLE SEATS IN AXLE CLAMP GROUP		
51 INCH AXLE SPACING		
MANUAL DUMP VALVE FOR AIR SUSPENSION WITHOUT GAUGE		
INDICATOR LIGHT FOR EACH REAR SUSPENSION CONTROL SWITCH		
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		
<b>Brake System</b>		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
BENDIX OIL COALESCING FILTER FOR AIR DRYER		
AIR DRYER MOUNTED INBOARD ON RH RAIL		
STEEL AIR TANKS MOUNTED AFT INSIDE AND/OR BELOW FRAME JUST FORWARD OF REAR SUSPENSION		
CLEAR FRAME RAILS 36 INCHES FROM BACK OF CAB INSIDE/OUTBOARD/BELOW BOTH FRAME RAILS		
BW DV-2 AUTO DRAIN VALVE WITH HEATER TO WET TANK; DRAIN VALVE CABLES ON ALL OTHER TANKS		

Description	Weight Front	Weight Rear
<b>Trailer Connections</b>		
UPGRADED CHASSIS MULTIPLEXING UNIT		
<b>Wheelbase &amp; Frame</b>		
6100MM (240 INCH) WHEELBASE		
11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	240	80
1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	220	410
3050MM (120 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 111 INCH TO 120 INCH	-100	450
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 174.45 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 159.45 in		
CALC'D FRAME LENGTH - OVERALL : 390.12		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 174.45 in		
CALCULATED FRAME SPACE LH SIDE : 91.62 in		
CALCULATED FRAME SPACE RH SIDE : 128.98 in		
SQUARE END OF FRAME		
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REAR MOST CROSSMEMBER		
HEAVY DUTY SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
14 INCH CHROMED STEEL BUMPER		
Loop step mounted below bumper	10	
REMOVABLE FRONT TOW HOOKS STORED ON THE CHASSIS FRAME	25	
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
FENDER AND FRONT OF HOOD MOUNTED FRONT M UDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
LEVEL FRAME RAILS (+/- 1%) WHEN CHASSIS IS LOADED TO FRONT AND REAR SUSPENSION RATINGS		
<b>Fuel Tanks</b>		

Description	Weight Front	Weight Rear
70 GALLON/264 LITER ALUMINUM FUEL TANK - LH 25 INCH DIAMETER FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS FUEL TANK(S) FORWARD PLAIN STEP FINISH FUEL TANK CAP(S) EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	5	
<b>Tires</b>		
MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES	196	
MICHELIN XDE M/S 11R22.5 14 PLY RADIAL REAR TIRES		56
<b>Hubs</b>		
CONMET PRESET PLUS IRON FRONT HUBS CONMET PRESET PLUS IRON REAR HUBS		
<b>Wheels</b>		
ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS	-8	
ALCOA LVL ONE 88367X ALUMINUM OUTSIDE, ACCURIDE 29637 STEEL INSIDE; 22.5X8.25 10- HUB PILOT DISC REAR WHEELS POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		-56
<b>Cab Exterior</b>		
114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB AIR CAB MOUNTING NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE FRONT FENDERS SET-BACK AXLE BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS LH AND RH GRAB HANDLES BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL	10	



Description	Weight Front	Weight Rear
STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS		
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
CAB FLOOR, TOE BOARD AND FIREWALL HEAT SHIELD	5	
DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED	4	
DUAL ELECTRIC HORNS		
DUAL HORN SHIELDS		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS		
REAR LICENSE PLATE MOUNT END OF FRAME		
HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS - LOW BEAM ONLY		
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS		
STANDARD FRONT TURN SIGNAL LAMPS		
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER		
ELECTRIC HORN WARNING SYSTEM FOR PARK BRAKE NOT SET WITH DOOR OPEN AND ALL IGNITION KEY POSITIONS		
COMPOSITE EXTERIOR SUN VISOR	10	
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S)	4	
TINTED WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, FRAME MOUNTED		

**Cab Interior**

Description	Weight Front	Weight Rear
OPAL GRAY VINYL INTERIOR		
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR		
MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR		
BLACK MATS WITH SINGLE INSULATION		
DASH MOUNTED ASH TRAY(S) WITHOUT LIGHTER		
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS AND ADDITIONAL CENTER COMPARTMENT WITHOUT NETTING		
CENTER STORAGE CONSOLE MOUNTED ON BACKWALL	20	
(2) CUP HOLDERS LH AND RH DASH		
GRAY/CHARCOAL WING DASH		
SMART SWITCH EXPANSION MODULE		
5 LB. FIRE EXTINGUISHER	10	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOMED DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF		
LH AND RH ELECTRIC DOOR LOCKS		
(1) 12 VOLT POWER SUPPLY IN DASH		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER	70	

Description	Weight Front	Weight Rear
BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT		
DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS	4	
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
GRAY MORDURA CLOTH DRIVER SEAT COVER		
GRAY MORDURA CLOTH PASSENGER SEAT COVER		
3 POINT FIXED D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10	
4-SPOKE 18 INCH (450MM) STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

### Instruments & Controls

WOODGRAIN DRIVER INSTRUMENT PANEL		
WOODGRAIN CENTER INSTRUMENT PANEL		
BLACK GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
97 DB BACKUP ALARM		3
ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
FUEL FILTER RESTRICTION INDICATOR		
EMISSIONS LIMITED IDLE ADJUST		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		

Description	Weight Front	Weight Rear
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, USB, FRONT AND REAR AUXILIARY INPUTS AND J1939		
DASH MOUNTED RADIO		
(2) RADIO SPEAKERS IN CAB		
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
POWER AND GROUND STUDS IN/UNDER DASH		
RADIO WIRING WITH POWER CUTOFF WHEN VEHICLE IN REVERSE GEAR		
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
VT-HU CONNECTIVITY PLATFORM HARDWARE		
2 YEARS DETROIT CONNECT BASE PACKAGE (VIRTUAL TECHNICIAN, DETROIT CONNECT PORTAL ACCESS) FOR VT-HU CONNECTIVITY PLATFORM		
NO ZONAR SYSTEMS (SCO)		
IGNITION SWITCH CONTROLLED ENGINE STOP		
TWO ON/OFF ROCKER SWITCHES IN THE DASH WITH INDICATOR LIGHTS AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT		
PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY PROGRAMMED TO SLOWEST SPEED WITH PARK BRAKE SET		
MARKER LIGHT/HEADLIGHT SWITCH WITH SEPARATE INTERRUPTER FOR CLEARANCE LIGHTS		
ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE		

Description	Weight Front	Weight Rear
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS		

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: L0225EB WHITE ELITE BC  
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS  
 PAINT  
 NO FUEL TANK CABINET PAINT  
 POWDER WHITE (N0006EA) REAR  
 WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
 SUNVISOR PAINTED SAME AS CAB COLOR A  
 STANDARD E COAT/UNDERCOATING

**Certification / Compliance**

CANADA CMVSS CERTIFICATION, EXCEPT  
 SALES CABS AND GLIDER KITS

**Sales Programs**

NO TELEMATICS SERVICE CONTRACT

**TOTAL VEHICLE SUMMARY**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	9835 lbs	7604 lbs	17439 lbs
Total Weight <sup>+</sup>	9835 lbs	7604 lbs	17439 lbs

**Extended Warranty**

TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING  
 COVERAGE \$550 CAP FEX APPLIES



**Prepared by:**  
CURRIE TRUCK CENTRE  
2 Currie Drive  
Midhurst, ON L9X 0N3  
Phone: 705 734-1953

(+) Weights shown are estimates only.  
If weight is critical, contact Customer Application Engineering.