

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Data Version		
SPECPRO21 DATA RELEASE VER 017		
Fuel Efficiency/Aero Package		
CASCADIA EVOLUTION (NO PREDICTIVE CRUISE) RAISED ROOF SLEEPER CAB FUEL EFFICIENCY PACKAGE 1.30; PAINTED BUMPER AND FAIRINGS		
Vehicle Configuration		
CASCADIA 125 INCH SLEEPER CAB 2017 MODEL YEAR SPECIFIED SET BACK AXLE - TRACTOR LH PRIMARY STEERING LOCATION	10,081	7,676
General Service		
TRACTOR/TRAILER CONFIGURATION DOMICILED, CANADA (OTHER THAN QUEBEC) LINEHAUL/LONG HAUL SERVICE GENERAL FREIGHT BUSINESS SEGMENT GENERAL FREIGHT COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE FREIGHTLINER LEVEL I WARRANTY EXPECTED FRONT AXLE(S) LOAD : 13200.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY 53,200.0 lbs EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs		



Description	Weight Front	Weight Rear
Tractor Service		
VAN TRAILER SINGLE (1) TRAILER		
Engine		
DETROIT DD15 14.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM		
Electronic Parameters		
65 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
Engine Equipment		
2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)		
STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER		
LOWER WINDSHIELD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER		
DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	10	
(4) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 4400 CCA THREADED STUD BATTERIES		
STEEL BATTERY BOX WITH ENCLOSED TRAY SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
PLASTIC BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	
PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS		
EATON SOLO ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH		
TORQUE LIMITING CLUTCH BRAKE		
ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING		

Description	Weight Front	Weight Rear
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
JACOBS COMPRESSION BRAKE		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH FRAME MOUNTED VERTICAL TAILPIPE (ROUTED UNDER/INSIDE RAIL)		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
13 FOOT 06 INCH (162 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
STANDARD CURVE BRIGHT UPPER STACK(S)		
RH CURVED VERTICAL TAILPIPE BACK OF CAB FRAME MOUNTED ROUTED BETWEEN RAILS OVER FRAME		
23 GALLON DIESEL EXHAUST FLUID TANK		
100 PERCENT DIESEL EXHAUST FLUID FILL		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD		
HORTON DRIVEMASTER ADVANTAGE ON/OFF FAN DRIVE		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
FULL FLOW OIL FILTER		
1400 SQUARE INCH RADIATOR		
ANTIFREEZE TO -60F, OAT (NITRITE & SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
HDEP VARIABLE SPEED COOLANT PUMP AND RADIATOR DRAIN VALVE		

Description	Weight Front	Weight Rear
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		
NO AIR INTAKE WARMER		
DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		

Transmission

EATON FULLER RTLO-16913A TRANSMISSION	90	40
---------------------------------------	----	----

Transmission Equipment

ALUMINUM CLUTCH HOUSING
 MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN
 PAINTED SHIFT LEVER, SOLID LINKAGE
 WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK
 SYNTHETIC TRANSMISSION LUBE

Front Axle and Equipment

DETROIT DA-F-13.3-3 13,300# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE		
NO FRONT AXLE ACCESSORIES		
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
2011/2013-FMVSS 121 FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
WABCO LONGSTROKE FRONT BRAKE CHAMBERS		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW THP-60 POWER STEERING		
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		

Description	Weight Front	Weight Rear
ROADRANGER SYNTHETIC FE 75W-90 FRONT AXLE LUBE		
Front Suspension		
13,300# TAPERLEAF FRONT SUSPENSION	30	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
DETROIT DA-RT-40.0-4 HT 40,000# R-SERIES TANDEM REAR AXLE		
3.58 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING		30
MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES		
MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		40
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE		
INDICATOR LIGHT AND BUZZER FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH		
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
2011/2013-FMVSS 121 REAR BRAKE LININGS		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
SKF SCOTSEAL PLUS XL REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
ROADRANGER SYNTHETIC FE 75W-90 REAR AXLE LUBE		
Rear Suspension		
AIRLINER 40,000# EXTRA DUTY REAR SUSPENSION		160

Description	Weight Front	Weight Rear
AIRLINER HIGH POSITION RIDE HEIGHT RESTRAINED AXLE SEATS IN AXLE CLAMP GROUP 51 INCH AXLE SPACING MANUAL DUMP VALVE FOR AIR SUSPENSION WITH 2 PSI OR 14 KPA INCREMENT GAUGE INDICATOR LIGHT AND BUZZER FOR EACH REAR SUSPENSION CONTROL SWITCH SINGLE AIR REAR SUSPENSION LEVELING VALVE TRANSVERSE CONTROL RODS REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		
Brake System		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES FIBER BRAID PARKING BRAKE HOSE STANDARD BRAKE SYSTEM VALVES STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM STD U.S. FRONT BRAKE VALVE RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE BW AD-9 BRAKE LINE AIR DRYER WITH HEATER BENDIX OIL COALESCING FILTER FOR AIR DRYER STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S); UNDER BATTERY BOX MOUNTED TANK DRAIN CABLES ACCESSIBLE THROUGH FAIRING KICKPLATE DOOR	20	
Trailer Connections		
15 FOOT COILED TRAILER AIR HOSE WITH 48 INCH TRACTOR, 12 INCH TRAILER LEADS 36 INCH STAINLESS STEEL SLIDE BAR WITH (2) 16 INCH SPRING TYPE AIR HOSE HANGERS COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER MOUNTED LH BACK OF CAB WITH GROUND ACCESS SWITCH AND INDICATOR LIGHT FOR PRIMARY RECEPTACLE CENTER PIN, LABELED TRLR-AUX	2	

Description	Weight Front	Weight Rear
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED LOWER LH BACK OF CAB		
NO SUPPLEMENTAL TRAILER CABLE WIRING		
SUPPLEMENTAL J560 7-WAY RECEPTACLE LOCATED WITH PRIMARY RECEPTACLE		
NO HIGH CURRENT TRAILER/BODY CABLE		
15 FOOT DETACHABLE COILED PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR WITH 48 INCH TRACTOR, 12 INCH TRAILER LEADS	2	

Wheelbase & Frame

5950MM (234 INCH) WHEELBASE		
11/32X3-1/2X10-3/16 INCH STEEL FRAME (8.73MMX258.8MM/0.344X10.19 INCH) 120KSI		
1450MM (57 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH		
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 94.04 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 82.27 in		
CALC'D FRAME LENGTH - OVERALL : 321.12		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 46.67 in		
CALCULATED FRAME SPACE LH SIDE : 19.18 in		
CALCULATED FRAME SPACE RH SIDE : 28.09 in		
FLANGED TAPERED END OF FRAME		
STANDARD WEIGHT ENGINE CROSSMEMBER		
INVERTED U TRACTOR CROSSMEMBER		10
HEAVY DUTY SUSPENSION CROSSMEMBER		30

Chassis Equipment

LH AND RH BACK OF CAB ACCESS	5	5
35 INCH (875MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS	8	7
PAINTED AERODYNAMIC BUMPER WITH CHROME OVERLAY AND ENHANCED AERODYNAMIC DEVICES	32	
REMOVABLE FRONT TOW HOOKS STORED ON THE CHASSIS FRAME	25	
BUMPER MOUNTING FOR (3) LICENSE PLATES		
BETTS B-7 STAINLESS STEEL MUDFLAP BRACKETS		10
NO REAR MUDFLAPS		-15

Description	Weight Front	Weight Rear
FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS EXCLUDING FIFTH WHEEL NO REAR QUARTER FENDERS NO TIRE PRESSURE CONTROL/SENSOR		
Fifth Wheel		
HOLLAND FW35 ILS 24.0 INCH AIR SLIDE FIFTH WHEEL - 2 INCH SLIDE INCREMENTS FIFTH WHEEL 559MM (22.0 INCHES) AHEAD OF SUSPENSION CENTERLINE FWD 5TH WHEEL SLIDE STOPS @ +20.00 202MM (7.94 INCH) FIFTH WHEEL HEIGHT INBOARD ANGLE - FIFTH WHEEL MOUNTING DASH MOUNTED CONTROL VALVE AND PLUMBING FOR FIFTH WHEEL LH FIFTH WHEEL RELEASE		60
Fuel Tanks		
150 GALLON/567 LITER ALUMINUM FUEL TANK - RH 150 GALLON/567 LITER ALUMINUM FUEL TANK - LH 25 INCH DIAMETER FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS FUEL TANK(S) AFT PLAIN STEP FINISH FUEL TANK CAP(S) DAVCO 482 FUEL/WATER SEPARATOR EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	20	20
150 GALLON/567 LITER ALUMINUM FUEL TANK - LH	20	20
Tires		
MICHELIN X LINE ENERGY Z 11R22.5 16 PLY RADIAL FRONT TIRES	10	
MICHELIN X MULTI ENERGY D 11R22.5 14 PLY RADIAL REAR TIRES		160
Hubs		
CONMET PRESET PLUS IRON FRONT HUBS	30	
CONMET PRESET PLUS IRON REAR HUBS		60
Wheels		

Description	Weight Front	Weight Rear
ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT 5.79 INSET ALUMINUM DISC FRONT WHEELS	-50	
ALCOA LVL ONE 88367X ALUMINUM OUTSIDE, ACCURIDE 50408 ACCU-LITE STEEL INSIDE; 22.5X8.25 10-HUB PILOT DISC REAR WHEELS POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY DEFLEKTOR AERODYNAMIC SEE-THROUGH REAR AXLE WHEEL COVERS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		-104
Cab Exterior		
125 INCH BBC ALUMINUM CONVENTIONAL CAB RH CAB DOOR(S) WITH 70 DEGREE DOOR STOP LH CAB DOOR(S) WITH 70 DEGREE DOOR STOP 72 INCH RAISED ROOF SLEEPERCAB RAISED ROOF AERODYNAMIC SPOILER		
20 INCH CAB/SLEEPERCAB SIDE EXTENDERS WITH BLACK FLEXIBLE ENDS AND CHASSIS FAIRING GAP FILLER PANEL UNDER CAB VANITY PANELS	10	10
PAINTED FRAME SIDE FAIRINGS TO BACK OF SIDE EXTENDERS LATCHED FRONT LEFT SIDE FAIRING PANEL FOR BATTERY ACCESS AERODYNAMIC SKIRT FOR CHASSIS FAIRINGS NO DRIVE WHEEL FAIRINGS - CHASSIS LH AND RH BAGGAGE DOORS AIR CAB MOUNTS NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE LH AND RH INTERIOR GRAB HANDLES CHROME GRILLE WITH INTEGRAL SURROUND AERODYNAMIC HOOD CASCADIA EVOLUTION NAMEPLATE ENGINE COMPARTMENT PREMIUM NOISE ABATEMENT AND INSULATION SINGLE AIR HORN UNDER LH DECK SINGLE ELECTRIC HORN	125	85

Description	Weight Front	Weight Rear
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS		
REAR LICENSE PLATE MOUNT END OF FRAME		
LED LOW BEAM AND HIGH BEAM HEADLIGHTS		
ROOF MOUNTED LED MARKER LIGHTS		
CLEAR FOG LIGHTS RECESSED IN BUMPER	6	
DAYTIME RUNNING LIGHTS		
FREIGHTLINER LED STOP/TAIL/TURN/BACKUP LIGHTS BY TRUCK-LITE		5
LED SIDE TURN SIGNAL		
(4) LED UTILITY LIGHTS: (2) SWIVEL MOUNTED LH AND RH OUTBOARD HIGH ON SIDE EXTENDERS AND (2) FLUSH MOUNTED BACK OF CAB	9	
UTILITY LIGHT SWITCH IN DASH		
DUAL BRIGHT FINISH HEATED AERODYNAMIC MIRRORS WITH INTEGRAL CONVEX AND LH AND RH REMOTE		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
RH AND LH BRIGHT FINISH HOOD/FENDER MOUNTED MIRRORS		
STANDARD SIDE/REAR REFLECTORS		
REAR REFLECTIVE DEVICE		
(2) PAINTED SLEEPER VENTS, LH AND RH		
SOLAR TINTED DOOR GLASS LH AND RH WITH TINTED FORWARD SIDE GLASS		
RH AND LH ELECTRIC POWERED WINDOWS		
LH AND RH SOLAR TINTED AND SCREENED CRANK OUT SLEEPER CAP WINDOWS		
2-PIECE SOLAR TINTED CURVED ROPED-IN WINDSHIELD		
8 LITER WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR		

Cab Interior

GRAY CLOTH INTERIOR		
STANDARD LH DOOR TRIM		
STANDARD RH DOOR TRIM		
BLACK MATS		
CARPET IN SLEEPER AREA	-10	
BLACK MATS IN BAGGAGE COMPARTMENT		
(1) DASH MOUNTED POWER OUTLET, LIGHTER AND ASH TRAY		

Description	Weight Front	Weight Rear
TALL CLOSET WITH APPLIANCE SHELF AND STORAGE CABINET		
MID-LEVEL REFRIGERATOR CABINET WITH TV SHELF AND STORAGE CABINETS		
FORWARD ROOF MOUNTED CONSOLE WITH CENTER LOCKING DOOR		
NO REAR FLOOR STORAGE		
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
STORAGE POCKET(S) MOUNTED INSIDE CABINET DOOR(S)		
40 INCH WIDE LIFTABLE LOWER BUNK		
FOLDABLE UPPER BUNK		
TENT STYLE BUNK RESTRAINT FOR LOWER BUNK		
DIGITAL FLUSH MOUNTED ALARM CLOCK IN SLEEPER		
PARCHMENT/SHALE WING DASH		
5 LB. FIRE EXTINGUISHER MOUNTED IN LH BAGGAGE COMPARTMENT	10	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
HVAC DUCTING WITH MAIN FRESH AIR FILTER		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
AUXILIARY HEATER/AIR CONDITIONER IN SLEEPER WITH CONSTANT TEMPERATURE WITH WEBASTO AIR TOP 2000 AIR HEATER	10	
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOOR AND BUNK ACTIVATED BAGGAGE COMPARTMENT LIGHTING SYSTEM		
PREMIUM CAB LIGHTING		
MID DOME LAMP SWITCH IN DASH		

Description	Weight Front	Weight Rear
PREMIUM SLEEPER LIGHTING		
LH AND RH ELECTRIC DOOR LOCKS		
QUILTED SPRING MATTRESS IN LOWER BUNK AND SPRING MATTRESS IN UPPER BUNK	30	30
(2) 12 VOLT POWER OUTLETS AT BASE OF BUNK		
CAB PRIVACY CURTAIN	5	
BUILT-IN REFRIGERATOR	20	20
TRIANGULAR REFLECTORS WITHOUT FLARES MOUNTED IN LH BAGGAGE COMPARTMENT	10	
ELITE 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT W/2 AIR LUMBAR,ACTIVE BOLSTER,INTEGRATED CUSHION EXTENSION, TILT,ADJUSTABLE SHOCK, MAP POCKET, HEAT & VENTILATION	10	
BASIC 2.0 HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT		
BLACK SUSPENSION COVER FOR DRIVER AND PASSENGER SEATS	4	
DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
MORDURA CLOTH DRIVER SEAT		
MORDURA CLOTH PASSENGER SEAT		
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS		
SLEEPER CURTAIN		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES		
DRIVER AND PASSENGER INTERIOR SUN VISORS WITH ILLUMINATED VANITY MIRRORS		

Instruments & Controls

ELECTRONIC FOOT ACCELERATOR
 LAZER BLACK DRIVER INSTRUMENT PANEL
 BLACK GAUGE BEZELS
 LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM
 (1) TRACTOR AND (1) TRAILER BRAKE APPLICATION AIR GAUGE
 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES

Description	Weight Front	Weight Rear
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
FUEL FILTER RESTRICTION INDICATOR		
EMISSIONS LIMITED IDLE ADJUST		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
ENGINE OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, USB, FRONT AND REAR AUXILIARY INPUTS AND J1939		
DASH MOUNTED RADIO		
STANDARD SPEAKER SYSTEM		
AM/FM/WB INTEGRATED AERO-ROOF ANTENNA		
COBRA 29 WX ST FACTORY INSTALLED CB RADIO WITH WEATHERBAND	5	
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION		
INTEGRATED AERO-ROOF CB ANTENNA		
TELEVISION ANTENNA		
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
DETROIT CONNECT VIRTUAL TECHNICIAN CONNECTIVITY PACKAGE (DETROIT ENGINES ONLY)		

Description	Weight Front	Weight Rear
2 YEARS DETROIT CONNECT VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE IGNITION SWITCH CONTROLLED ENGINE STOP ONE EXTRA SWITCH IN DASH WITH INDICATOR LAMP AND WIRE TO CHASSIS AT BACK OF CAB/SLEEPER NO PRE TRIP SYSTEM TEST STEERING WHEEL MOUNTED ELECTRIC HORN CONTROL BW TRACTOR PROTECTION VALVE TRAILER HAND CONTROL BRAKE VALVE DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006B WHITE ELITE BC
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
 PAINT
 CHASSIS SIDE FAIRINGS PAINTED SAME AS
 LOWER CAB SECTION OR FENDER
 NO FUEL TANK CABINET PAINT
 POWDER WHITE (N0006EA) REAR
 WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
 BUMPER PAINTED SAME AS FENDERS/LOWER
 SECTION OF CAB

Certification / Compliance

CANADA CMVSS CERTIFICATION, EXCEPT
 SALES CABS AND GLIDER KITS

T O T A L V E H I C L E S U M M A R Y



Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	10606 lbs	8369 lbs	18975 lbs
<hr/>			
Total Weight ⁺	10606 lbs	8369 lbs	18975 lbs

Extended Warranty

EW4: DD15 HWY \$0 DED 5 YEARS/500,000 MILES/805,000 KM FULL
COVERAGE. FEX APPLIES
TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING
COVERAGE \$550 CAP FEX APPLIES

(+) Weights shown are estimates only.
If weight is critical, contact Customer Application Engineering.

