

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Bright Work Packages		
BRIGHT WORK PACKAGE 1 - CHROMED: AIR INTAKE, GRILLE, HEADLIGHT BEZEL AND 14 INCH ROUND POLISHED AIR HORN COMBINED OPTION COSTS OF THE SELECTED CODES FROM THE BRIGHT WORK PACKAGE 1		
Vehicle Configuration		
M2 106 CONVENTIONAL CHASSIS 2017 MODEL YEAR SPECIFIED SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION LH PRIMARY STEERING LOCATION	5,759	3,503
General Service		
TRUCK CONFIGURATION DOMICILED, CANADA (OTHER THAN QUEBEC) PICKUP AND DELIVERY/SHORT HAUL SERVICE GENERAL FREIGHT BUSINESS SEGMENT GENERAL FREIGHT COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE MEDIUM TRUCK WARRANTY EXPECTED FRONT AXLE(S) LOAD : 10000.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 17500.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 27500.0 lbs EXPECTED GROSS COMBINATION WEIGHT : 0.0 lbs		

Description	Weight Front	Weight Rear
Truck Service		
DRY VAN BODY EXPECTED TRUCK BODY LENGTH : 22.0 ft EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
Engine		
DD5 5.1L 4 CYL 230 HP @ 2200 RPM, 2600 GOV RPM, 660 LB/FT @ 1200 RPM	270	-190
Electronic Parameters		
65 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED PTO MODE CANCEL VEHICLE SPEED - 5 MPH PTO MODE RPM INCREMENT - 25 RPM ONE REMOTE PTO SPEED REMOTE PTO SPEED 1 SETTING - 900 RPM		
Engine Equipment		
2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LEFT SIDE OF HOOD) STANDARD OIL PAN ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE (2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES BATTERY BOX FRAME MOUNTED STANDARD BATTERY JUMPERS SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN NON-POLISHED BATTERY BOX COVER		

Description	Weight Front	Weight Rear
WABCO 20.0 CFM SINGLE CYLINDER AIR COMPRESSOR		
STANDARD MECHANICAL AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE		
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND DASH MOUNTED SINGLE REGENERATION REQUEST/INHIBIT SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH STANDARD HORIZONTAL TAILPIPE		
6 GALLON DIESEL EXHAUST FLUID TANK		
100 PERCENT DIESEL EXHAUST FLUID FILL		
LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
BORG WARNER ELECTRONIC VISCOUS FAN DRIVE		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DETROIT SUPPLIED ENGINE MOUNTED FUEL FILTER		
FULL FLOW OIL FILTER		
950 SQUARE INCH ALUMINUM RADIATOR		
ANTIFREEZE TO -60F, OAT (NITRITE & SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
RADIATOR DRAIN VALVE		
LOWER RADIATOR GUARD		
PHILLIPS-TEMRO 750 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		

Description	Weight Front	Weight Rear
DELCO 12V 29MT STARTER WITH INTEGRATED MAGNETIC SWITCH		
Transmission		
ALLISON 2500 HS AUTOMATIC TRANSMISSION, NO PTO PROVISION		
Transmission Equipment		
ALLISON VOCATIONAL PACKAGE 354 - AVAILABLE ON 1000/2000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, EVS, HS, MH, PTS AND SPS		
ALLISON VOCATIONAL RATING FOR HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
PRIMARY MODE GEARS, 6 FORWARD GEARS WITH MANUAL SELECTION FOR 3, 2 AND 1, AVAILABLE FOR 1000/2000 PRODUCT FAMILIES ONLY		
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE PRESELECT RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
ENGINE BRAKE RANGE ALTERNATE PRESELECT R ECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
LOAD BASED SHIFT SCHEDULE AND VEHICLE ACCELERATION CONTROL RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED VOCATIONAL USAGE		
NEUTRAL AT STOP - DISABLED, FUELSENSE - DISABLED		
DISABLE - NEUTRAL RANGE ASSIST		
DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
VEHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT END OF FRAME		

Description	Weight Front	Weight Rear
ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
DASH MOUNTED T-HANDLE CABLE SHIFT CONTROL WITH PARK BRAKE POSITION		
TRANSMISSION PROGNOSTICS - DISABLED (N/A) 2013, FOR USE IN 1000/2000 ONLY		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

DETROIT DA-F-10.0-3 10,000# FF1 71.5 KPI/3.74
 DROP SINGLE FRONT AXLE
 BOSCH HYDRAULIC PIN-SLIDE DISC FRONT
 BRAKES
 NON-ASBESTOS FRONT BRAKE LINING
 FRONT DISC BRAKE ROTORS
 FRONT OIL SEALS
 VENTED FRONT HUB CAPS WITH WINDOW,
 CENTER AND SIDE PLUGS - OIL
 STANDARD SPINDLE NUTS FOR ALL AXLES
 TRW THP-60 POWER STEERING
 POWER STEERING PUMP
 2 QUART SEE THROUGH POWER STEERING
 RESERVOIR
 SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

10,000# TAPERLEAF FRONT SUSPENSION
 MAINTENANCE FREE RUBBER BUSHINGS -
 FRONT SUSPENSION
 NO FRONT SUSPENSION SPRING BRACKET
 OPTIONS
 FRONT SHOCK ABSORBERS

Rear Axle and Equipment

DETROIT DA-RS-17.5-4 17,500# R-SERIES SINGLE REAR AXLE	-15
6.14 REAR AXLE RATIO	
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING	

Description	Weight Front	Weight Rear
MXL 16T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	35	35
BOSCH HYDRAULIC PIN-SLIDE DISC REAR BRAKES		
NON-ASBESTOS REAR BRAKE LINING		
REAR DISC BRAKE ROTORS		
SKF SCOTSEAL CLASSIC REAR OIL SEALS		
REAR AXLE MOUNTED AIR OPERATED DRUM PARK BRAKE		
SYNTHETIC 75W-90 REAR AXLE LUBE		
Rear Suspension		
AIRLINER 18,000# REAR SUSPENSION		-20
AIRLINER MID POSITION RIDE HEIGHT		
STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
IGNITION CONTROLLED ELECTRIC DUMP SWITCH FOR AIR SUSPENSION WITH AUTOFILL OVERRIDE VALVE		
REAR AIR SUSPENSION DUMP VALVE WITH AUTOFILL FOR IGNITION OFF AND >5 MPH, INCLUDE OVERRIDE CONTROL AND BUZZER ON DUMP VALVE SWITCH		
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - ONE AXLE (AIR RIDE SUSPENSION)		
Brake System		
HYDRAULIC BRAKE PACKAGE WITH OPTIONAL AIR SUPPLY	-20	-120
WABCO HYDRAULIC 4S/4M ABS WITHOUT TRACTION CONTROL		
HYDRAULIC TUBING WITH NYLON AND FABRIC/WIRE BRAID CHASSIS AIR LINES	10	10
NYLON PARKING BRAKE HOSE		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
AIR DRYER MOUNTED UNDER HOOD		
ONE STEEL AIR ACCESSORY RESERVOIR		
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)		
Trailer Connections		

Description	Weight Front	Weight Rear
UPGRADED CHASSIS MULTIPLEXING UNIT		
UPGRADED BULKHEAD MULTIPLEXING UNIT		
NO HIGH CURRENT TRAILER/BODY CABLE		
Wheelbase & Frame		
6400MM (252 INCH) WHEELBASE		
11/32X3-1/2X10-3/16 INCH STEEL FRAME (8.73MMX258.8/0.344X10.19 INCH) 80KS	370	110
3050MM (120 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 111 INCH TO 120 INCH	-70	300
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 186.45 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 183.45 in		
CALC'D FRAME LENGTH - OVERALL : 401.39		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 186.45 in		
CALCULATED FRAME SPACE LH SIDE : 158.12 in		
CALCULATED FRAME SPACE RH SIDE : 191.72 in		
SQUARE END OF FRAME		
REAR TOW HOOKS		10
FRONT CLOSING CROSSMEMBER		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REAR MOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
Chassis Equipment		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED	15	
BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
LEVEL FRAME RAILS (+/- 1%) WHEN CHASSIS IS LOADED TO FRONT AND REAR SUSPENSION RATINGS		
Fuel Tanks		

Description	Weight Front	Weight Rear
80 GALLON/302 LITER RECTANGULAR ALUMINUM FUEL TANK - LH RECTANGULAR FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS FUEL TANK(S) FORWARD POLISHED STAINLESS STEEL STEP FINISH FUEL TANK CAP(S) DETROIT FUEL/WATER SEPARATOR WITH BYPASS, WIF, AND HAND PRIMER EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	40 -5	10
Tires		
BRIDGESTONE ECOPIA R268 11R22.5 14 PLY RADIAL FRONT TIRES	12	
BRIDGESTONE ECOPIA M710 11R22.5 14 PLY RADIAL REAR TIRES		52
Hubs		
CONMET PRESET IRON FRONT HUBS GUNITE IRON REAR AXLE HUBS		
Wheels		
ACCURIDE 41644 ACCU-LITE 22.5X8.25 10-HUB PILOT 5.72 INSET ALUMINUM DISC FRONT WHEELS ACCURIDE 50487 ACCU-LITE 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS POLISHED FRONT WHEELS; INSIDE AND OUTSIDE FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES	-50	
Cab Exterior		
106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB AIR CAB MOUNTING NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE LH AND RH GRAB HANDLES HOOD MOUNTED CHROMED PLASTIC GRILLE		

Description	Weight Front	Weight Rear
CHROME HOOD MOUNTED AIR INTAKE GRILLE		
FIBERGLASS HOOD		
HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5	
SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK	4	
SINGLE ELECTRIC HORN		
SINGLE HORN SHIELD		
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS		
REAR LICENSE PLATE MOUNT END OF FRAME		
INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL		
LED AERODYNAMIC MARKER LIGHTS		
DAYTIME RUNNING LIGHTS		
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS		
STANDARD FRONT TURN SIGNAL LAMPS		
DUAL WEST COAST BRIGHT FINISH MIRRORS		
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
STANDARD SIDE/REAR REFLECTORS		
DUAL LEVEL CAB ENTRY STEPS ON BOTH SIDES		
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S)	4	
1-PIECE TINTED ROPED-IN WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, FRAME MOUNTED		

Cab Interior

OPAL GRAY CLOTH INTERIOR
 MOLDED PLASTIC DOOR PANEL
 MOLDED PLASTIC DOOR PANEL
 BLACK MATS WITH SINGLE INSULATION
 FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING

Description	Weight Front	Weight Rear
IN DASH STORAGE BIN		
PLASTIC MANIFEST BOX - LH DOOR		
(2) CUP HOLDERS LH AND RH DASH		
GRAY/CHARCOAL FLAT DASH		
2-1/2 LB. FIRE EXTINGUISHER	5	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER		
STANDARD HVAC DUCTING WITH SNOW SHIELD FOR FRESH AIR INTAKE		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOMED DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF		
LH AND RH ELECTRIC DOOR LOCKS		
(1) 12 VOLT POWER SUPPLY IN DASH		
TRIANGULAR REFLECTORS WITHOUT FLARES	10	
BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30	
2 MAN TOOL BOX MID BACK NON SUSPENSION PASSENGER SEAT	20	
INBOARD DRIVER SEAT ARMREST, NO PASSENGER SEAT ARMREST	2	
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
GRAY MORDURA CLOTH DRIVER SEAT COVER		
GRAY MORDURA CLOTH PASSENGER SEAT COVER		
BLACK SEAT BELTS		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN	10	
4-SPOKE 18 INCH (450MM) STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

Instruments & Controls

STOCK# 3211

Description	Weight Front	Weight Rear
GRAY DRIVER INSTRUMENT PANEL		
GRAY CENTER INSTRUMENT PANEL		
BLACK GAUGE BEZELS		
LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
SINGLE AIR PRESSURE GAUGE FOR HYDRAULIC BRAKES WITH AIR PROVISION		
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
97 DB BACKUP ALARM		3
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY WITH ECM STARTER LOCKOUT		
ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
EMISSIONS LIMITED IDLE ADJUST		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
NO LANE DEPARTURE WARNING SYSTEM		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
OVERHEAD INSTRUMENT PANEL		
AM/FM/WB RADIO WITH BLUETOOTH AND MICROPHONE, FRONT USB PORT, FRONT AND REAR AUXILIARY INPUTS AND J1939		
DASH MOUNTED RADIO		
(2) RADIO SPEAKERS IN CAB		
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
VT-HU CONNECTIVITY PLATFORM HARDWARE		

Description	Weight Front	Weight Rear
3 YEARS DETROIT CONNECT BASE PACKAGE (VIRTUAL TECHNICIAN, DETROIT CONNECT PORTAL ACCESS) FOR VT-HU CONNECTIVITY PLATFORM NO ZONAR SYSTEMS (SCO) IGNITION SWITCH CONTROLLED ENGINE STOP ONE ON/OFF ROCKER SWITCH IN THE DASH WITH INDICATOR LIGHT AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FLASH, WITH SMART SWITCH DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY PROGRAMMED TO SLOWEST SPEED WITH PARK BRAKE SET MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH ONE VALVE PARKING BRAKE SYSTEM WITH SHIFTER CONTROLLED AUTOPARK AND WARNING INDICATOR SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS NO MISCELLANEOUS GAUGES		
Design		
PAINT: ONE SOLID COLOR		
Color		
CAB COLOR A: L0006EB WHITE ELITE BC BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT NO FUEL TANK CABINET PAINT POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) STANDARD E COAT/UNDERCOATING		
Certification / Compliance		
CANADA CMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		
T O T A L V E H I C L E S U M M A R Y		

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	6514 lbs	3688 lbs	10202 lbs
<hr/>			
Total Weight ⁺	6514 lbs	3688 lbs	10202 lbs

(+) Weights shown are estimates only.
If weight is critical, contact Customer Application Engineering.