

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>Vehicle Configuration</b>		
122SD CONVENTIONAL CHASSIS	9,184	6,816
2018 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRACTOR		
LH PRIMARY STEERING LOCATION		
<b>General Service</b>		
TRACTOR/TRAILER CONFIGURATION		
DOMICILED, CANADA (OTHER THAN QUEBEC)		
CONSTRUCTION SERVICE		
CONSTRUCTION BUSINESS SEGMENT		
DIRT/SAND/ROCK COMMODITY		
TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN TRANSIT, IS SPENT ON NON-PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
MAINTAINED GRAVEL OR CRUSHED ROCK - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
FREIGHTLINER LEVEL II WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 14600.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 60600.0 lbs		
EXPECTED GROSS COMBINATION WEIGHT : 120000.0 lbs		
<b>Tractor Service</b>		
FRAMED END DUMP (NON-TRANSFER) TRAILER		
SINGLE (1) TRAILER		
<b>Engine</b>		
DETROIT DD15 14.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1650 LB/FT @ 975 RPM		

STOCK# 3273

Description	Weight Front	Weight Rear
<b>Electronic Parameters</b>		
65 MPH ROAD SPEED LIMIT		
CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
<b>Engine Equipment</b>		
2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION		
2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)		
STANDARD OIL PAN		
ENGINE MOUNTED OIL CHECK AND FILL		
ONE PIECE VALVE COVER		
DUAL SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED HIGH CAPACITY AIR CLEANER		
DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE	10	
(4) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 4400 CCA THREADED STUD BATTERIES	50	10
STEEL BATTERY BOX WITH ENCLOSED TRAY		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED DIAMOND PLATE BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	
EATON SOLO ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH		
TORQUE LIMITING CLUTCH BRAKE		
ZERK FITTINGS WITH EXTENSION HOSES AT CLUTCH RELEASE BEARING AND X-SHAFT		
MECHANICAL CLUTCH CONTROL		
BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
STANDARD MECHANICAL AIR COMPRESSOR GOVER NOR		
AIR COMPRESSOR DISCHARGE LINE		
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		

Description	Weight Front	Weight Rear
JACOBS COMPRESSION BRAKE		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH DUAL CAB MOUNTED VERTICAL TAILPIPES	55	33
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
12 FOOT 06 INCH (150 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
STANDARD CURVE BRIGHT UPPER STACK(S) AND ELBOW(S)		
DUAL CURVED VERTICAL TAILPIPES B-PILLAR MOUNTED		
23 GALLON DIESEL EXHAUST FLUID TANK		
100 PERCENT DIESEL EXHAUST FLUID FILL		
NON-POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER	15	15
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
DUAL STAINLESS STEEL MUFFLER/TAILOPIPE SHIELDS		
HORTON DRIVEMASTER ADVANTAGE ON/OFF FAN DRIVE		
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
FULL FLOW OIL FILTER		
1500 SQUARE INCH ALUMINUM RADIATOR		
ANTIFREEZE TO -60F, OAT (NITRITE & SILICATE FREE) EXTENDED LIFE COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE		
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
ALUMINUM FLYWHEEL HOUSING		

Description	Weight Front	Weight Rear
DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		
<b>Transmission</b>		
EATON FULLER RTLO-16918B TRANSMISSION	90	40
<b>Transmission Equipment</b>		
NO TCU-LBSS_VAC		
CAST IRON CLUTCH HOUSING		
CUSTOMER INSTALLED CHELSEA 340 SERIES PTO		
PTO MOUNTING, BOTTOM OF MAIN TRANSMISSION		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN		
PAINTED SHIFT LEVER, SOLID LINKAGE		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
SYNTHETIC TRANSMISSION LUBE		
<b>Front Axle and Equipment</b>		
DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE		
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
2011/2013-FMVSS 121 FRONT BRAKE LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
FRONT BRAKE DUST SHIELDS	5	
SKF SCOTSEAL PLUS XL FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
WABCO LONGSTROKE FRONT BRAKE CHAMBERS		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
STANDARD KING PIN BUSHINGS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
STANDARD CUPS AND CONES (WHEEL BEARINGS) FRONT AND REAR		

Description	Weight Front	Weight Rear
SYNTHETIC 75W-90 FRONT AXLE LUBE		
<b>Front Suspension</b>		
14,600# TAPERLEAF FRONT SUSPENSION	130	
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
<b>Rear Axle and Equipment</b>		
RT-46-164P 46,000# R-SERIES TANDEM REAR AXLE		580
3.91 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
RPL25SD MERITOR MAIN DRIVELINE	40	40
RPL20 MERITOR INTERAXLE DRIVELINE		
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		40
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE		
INDICATOR LIGHT AND BUZZER FOR EACH INTERAXLE LOCKOUT SWITCH		
INDICATOR LIGHT AND BUZZER FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH		
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
2011/2013-FMVSS 121 REAR BRAKE LININGS		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
CONMET CAST IRON REAR BRAKE DRUMS		
REAR BRAKE DUST SHIELDS		10
SKF SCOTSEAL PLUS XL REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		20
MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>Rear Suspension</b>		
AIRLINER 46,000# REAR SUSPENSION		480
AIRLINER HIGH POSITION RIDE HEIGHT		

Description	Weight Front	Weight Rear
RESTRAINED AXLE SEATS IN AXLE CLAMP GROUP		
51 INCH AXLE SPACING		
MANUAL DUMP VALVE FOR AIR SUSPENSION WITH GAUGE		
INDICATOR LIGHT AND BUZZER FOR EACH REAR SUSPENSION CONTROL SWITCH		
SINGLE AIR REAR SUSPENSION LEVELING VALVE		
TRANSVERSE CONTROL RODS		
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		
<b>Brake System</b>		
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
FIBER BRAID PARKING BRAKE HOSE		
STANDARD BRAKE SYSTEM VALVES		
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
STD U.S. FRONT BRAKE VALVE		
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
BENDIX OIL COALESCING FILTER FOR AIR DRYER		
STEEL AIR BRAKE RESERVOIRS		
PULL CABLES ON ALL AIR RESERVOIR(S)		
EXTERNAL CHARGING GLADHAND	5	
<b>Trailer Connections</b>		
15 FOOT COILED TRAILER AIR HOSE WITH 48 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
36 INCH STAINLESS STEEL SLIDE BAR WITH (2) SPRING TYPE AIR HOSE HANGERS	2	
COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER		
SWITCH AND INDICATOR LIGHT FOR PRIMARY RECEPTACLE CENTER PIN, LABELED TRLR-AUX		
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE FRAME MOUNTED AFT CAB		
SUPPLEMENTAL J560 7-WAY RECEPTACLE LOCATED WITH PRIMARY RECEPTACLE		

Description	Weight Front	Weight Rear
15 FOOT DETACHABLE COILED PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR WITH 48 INCH TRACTOR, 12 INCH TRAILER LEADS	2	
<b>Wheelbase &amp; Frame</b>		
5850MM (230 INCH) WHEELBASE		
7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	480	50
1450MM (57 INCH) REAR FRAME OVERHANG		
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH		
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 114.25 in		
CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 94.32 in		
CALC'D FRAME LENGTH - OVERALL : 317.12		
CALC'D SPACE AVAILABLE FOR DECKPLATE : 10090.23 in		
CALCULATED FRAME SPACE LH SIDE : 30.82 in		
CALCULATED FRAME SPACE RH SIDE : 16.7 in		
FLANGED TAPERED END OF FRAME		
STANDARD WEIGHT ENGINE CROSSMEMBER		
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
INVERTED U TRACTOR CROSSMEMBER		10
HEAVY DUTY SUSPENSION CROSSMEMBER		30
STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER		
<b>Chassis Equipment</b>		
LH BACK OF CAB ACCESS		
35 INCH (875MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS	8	7
12 INCH CHROMED STEEL HEAVY DUTY BUMPER	30	-5
CENTER STEP CUTOUT IN BUMPER		
REMOVABLE FRONT TOW HOOKS STORED ON THE CHASSIS FRAME	25	
SINGLE LICENSE PLATE BRACKET BELOW BUMPER		
BETTS B-7 STAINLESS STEEL MUDFLAP BRACKETS		10
NO REAR MUDFLAPS		-15
FRONT CAB MOUNTED MUDFLAPS AND HOOD MOUNTED SPLASH SHIELDS		

Description	Weight Front	Weight Rear
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS EXCLUDING FIFTH WHEEL		
<b>Fifth Wheel</b>		
HOLLAND FW35 24.5 INCH AIR SLIDE FIFTH WHEEL - HIGH MOUNT - CYLINDER FORWARD - 1.5 INCH SLIDE INCREMENTS FIFTH WHEEL 571MM (22.5 INCHES) AHEAD OF SUSPENSION CENTERLINE FWD 5TH WHEEL SLIDE STOPS @ +21.00 211MM (8.31 INCH) FIFTH WHEEL HEIGHT INBOARD ANGLE - FIFTH WHEEL MOUNTING DASH MOUNTED CONTROL VALVE AND PLUMBING FOR FIFTH WHEEL LH FIFTH WHEEL RELEASE		170
<b>Fuel Tanks</b>		
100 GALLON/378 LITER ALUMINUM FUEL TANK - RH	105	20
140 GALLON/529 LITER ALUMINUM FUEL TANK - LH	30	
80 GALLON ALUMINUM HYDRAULIC RESERVOIR, RH WITH 1-1/4 INCH NPT TOP AND BOTTOM END FITTINGS 25 INCH DIAMETER FUEL TANK(S) PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS FUEL TANK(S) AFT PLAIN STEP FINISH FUEL TANK CAP(S) EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	65	60
<b>Tires</b>		
MICHELIN X WORKS Z 12R22.5 16 PLY RADIAL FRONT TIRES	76	
MICHELIN XDN2 11R22.5 14 PLY RADIAL REAR TIRES		152
<b>Hubs</b>		
CONMET PRESET PLUS IRON FRONT HUBS CONMET PRESET PLUS IRON REAR HUBS		
<b>Wheels</b>		



Description	Weight Front	Weight Rear
ALCOA ULTRA ONE 89U64X 22.5X9.00 10-HUB PILOT 5.99 INSET ALUMINUM FRONT WHEELS	-28	
ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS POLISHED FRONT WHEELS; OUTSIDE ONLY POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY FRONT TIRE/DISC WHEEL STATIC BALANCING WITH LEAD-FREE WEIGHTS NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		-264
<b>Cab Exterior</b>		
122 INCH BBC ALUMINUM CONVENTIONAL CAB RH CAB DOOR(S) WITH 70 DEGREE DOOR STOP LH CAB DOOR(S) WITH 70 DEGREE DOOR STOP 48 INCH MID-ROOF SLEEPER CAB	180	240
CAB/SLEEPER SIDE EXTENDERS - 102 INCH, 18/0	15	20
22 INCH LH AND RH BAGGAGE DOORS WITH INTERIOR PULL CABLE SEVERE DUTY VOCATIONAL AIR CAB MOUNTS NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE FRONT FENDERS LH AND RH EXHAUST MOUNTED EXTERIOR GRAB HANDLES WITH INTERIOR GRAB HANDLES BRIGHT FINISH BEZEL WITH STYLIZED TILT HANDLE STAINLESS STEEL GRILLE CHROME HOOD MOUNTED AIR INTAKE GRILLE FIBERGLASS HOOD WITH REINFORCED FENDERS 122SD NAMEPLATE ENGINE COMPARTMENT PREMIUM NOISE ABATEMENT AND INSULATION		
FOUR 29 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS SINGLE ELECTRIC HORN FOUR HORN SHIELDS DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS REAR LICENSE PLATE MOUNT END OF FRAME	12	

Description	Weight Front	Weight Rear
HALOGEN COMPOSITE HEADLAMPS		
FREIGHTLINER LED MARKER LIGHTS INTEGRAL WITH EXTERIOR SUN VISOR		
LED ACCENT LIGHTS ON HOOD AIR INTAKES AND LOWER EDGE OF CAB AND SLEEPER	15	
CUSTOMER FURNISHED ROADLAMPS - WIRING, SWITCH AND BRACKETS (IF APPLICABLE) ONLY		
DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH		
FREIGHTLINER LED STOP/TAIL/TURN/BACKUP LIGHTS BY TRUCK-LITE		5
STANDARD FRONT TURN SIGNAL LAMPS		
(2) FLUSH UTILITY LIGHTS MOUNTED BACK OF CAB/SLEEPER AND (2) CHROME SWIVEL UTILITY LIGHTS MOUNTED LH AND RH HIGH OUTBOARD ON SIDE EXTENDERS	12	
DUAL BRIGHT FINISH HEATED AERODYNAMIC MIRRORS WITH INTEGRAL CONVEX, LIGHTS AND DUAL AXIS LH AND RH REMOTE	20	
DOOR MOUNTED MIRRORS		
102 INCH EQUIPMENT WIDTH		
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS		
RH DOWN VIEW MIRROR		
STANDARD SIDE/REAR REFLECTORS		
REAR REFLECTIVE DEVICE		
RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER		
(2) PAINTED SLEEPER VENTS, LH AND RH		
STAINLESS STEEL EXTERIOR SUN VISOR WITH INTEGRAL MARKER LIGHTS	16	
TINTED DOOR GLASS		
RH AND LH ELECTRIC POWERED WINDOWS		
2-PIECE TINTED CURVED BONDED WINDSHIELD		
8 LITER WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITHOUT FLUID LEVEL INDICATOR		

**Cab Interior**

GRAPHITE BLACK CHAPARRAL VINYL INTERIOR  
 CLASSIC SLATE GRAY HARD TRIM  
 LH DOOR TRIM WITH ADDITIONAL ARCTIC SEAL PACKAGE

Description	Weight Front	Weight Rear
RH DOOR TRIM WITH ADDITIONAL ARCTIC SEAL PACKAGE		
CAB BLACK FLOOR MATS WITH PREMIUM NOISE ABATEMENT AND INSULATION		
BLACK FLOOR MATS WITH PREMIUM NOISE ABATEMENT AND INSULATION IN SLEEPER	10	
FULL UNDER BUNK/BAGGAGE COMPARTMENT LINER WITH BLACK MATS, PREMIUM NOISE ABATEMENT/INSULATION AND REMOVABLE PARTITIONS		
DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE		
FORWARD ROOF MOUNTED CONSOLE WITH DOORS RH AND LH		
LH AND RH DOOR MAP POCKETS		
CLOTHES ROD IN SLEEPER		
35 INCH WIDE LIFTABLE LOWER BUNK		
LOWER BUNK RESTRAINT		
DIGITAL FLUSH MOUNTED ALARM CLOCK IN SLEEPER		
(3) CUP HOLDERS, LH, CENTER AND RH DASH AGATE/SLATE GRAY WING DASH		
2-1/2 LB. FIRE EXTINGUISHER	5	
FIRST AID KIT	2	
HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
HVAC DUCTING WITH MAIN FRESH AIR FILTER MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
AUXILIARY HEATER/AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
STANDARD PLUMBING WITH INSULATED AUXILIARY HEATER PLUMBING UNDER CAB DECK ONLY		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
BINARY CONTROL, R-134A		
CAB AND SLEEPER PREMIUM NOISE ABATEMENT AND INSULATION		
AUTOMATIC SELF-RESET CIRCUIT BREAKERS		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		

Description	Weight Front	Weight Rear
DOOR AND BUNK ACTIVATED LH AND RH BUNK MOUNTED BAGGAGE COMPARTMENT LIGHTS		
DOOR ACTIVATED DOME/RED MAP LIGHTS LH AND RH OVERHEAD, COURTESY LIGHTS IN EACH DOOR AND FOOT WELL LIGHTS LH AND RH WITH DASH SWITCH		
(1) DOME LIGHT AND (1) READING LIGHT WITH DASH AND BUNK SWITCHES		
LH AND RH ELECTRIC DOOR LOCKS		
80X34X8 INCH QUILTED SPRING MATTRESS IN SLEEPER	15	15
(2) 12 VOLT POWER OUTLETS IN SLEEPER PANEL AND RH LOWER B-PILLAR COVER		
TRIANGULAR REFLECTORS WITHOUT FLARES MOUNTED IN RH BAGGAGE COMPARTMENT	10	
PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER	40	
BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT		
DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS	4	
BLACK MORDURA CLOTH DRIVER SEAT COVER		
BLACK MORDURA CLOTH PASSENGER SEAT COVER		
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND PASSENGER SEAT BELTS		
SLEEPER CURTAIN		
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

### Instruments & Controls

BRIGHT ARGENT FINISH GAUGE BEZELS  
 BANDON DRIFTWOOD DRIVER INSTRUMENT PANEL  
 BANDON DRIFTWOOD CENTER INSTRUMENT PANEL  
 LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM  
 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES

Description	Weight Front	Weight Rear
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
97 DB BACKUP ALARM		3
ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)		
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
ICU4ME DRIVER MESSAGE CENTER WITH GRAPHICAL DISPLAY, WHITE FACE GAUGES, DIAGNOSTICS AND DATA LINKED		
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
2 INCH ELECTRIC FUEL GAUGE		
FUEL FILTER RESTRICTION INDICATOR		
EMISSIONS LIMITED IDLE ADJUST		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS		
ELECTRIC ENGINE OIL PRESSURE GAUGE OVERHEAD INSTRUMENT PANEL		
AM/FM/WB RADIO WITH BLUETOOTH AND MICROP HONE, FRONT USB PORT, FRONT AND REAR AUXILIARY INPUTS AND J1939		
DASH MOUNTED RADIO		
(4) RADIO SPEAKERS: (1) COAXIAL IN EACH DOOR AND (2) COAXIALS IN SLEEPER		
COBRA 29NW LTD CLASSIC FACTORY INSTALLED CB RADIO	5	
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION WITH MODIFIED FACE PLATE		
MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNTED ANTENNA SYSTEM		
ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITHOUT ODOMETER		

Description	Weight Front	Weight Rear
STANDARD VEHICLE SPEED SENSOR ELECTRONIC 3000 RPM TACHOMETER VT-HU CONNECTIVITY PLATFORM HARDWARE 2 YEARS DETROIT CONNECT BASE PACKAGE (VIRTUAL TECHNICIAN, DETROIT CONNECT PORTAL ACCESS) FOR VT-HU CONNECTIVITY PLATFORM NO ZONAR SYSTEMS (SCO) IGNITION SWITCH CONTROLLED ENGINE STOP ONE EXTRA SWITCH IN DASH WITH INDICATOR LAMP AND WIRE TO CHASSIS AT BACK OF CAB/SLEEPER BW TRACTOR PROTECTION VALVE TRAILER HAND CONTROL BRAKE VALVE 2 INCH TURBO AIR PRESSURE GAUGE DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY MARKER LIGHT/HEADLIGHT SWITCH WITH SEPARATE INTERRUPTER FOR CLEARANCE LIGHTS TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR GROTE TURN SIGNAL SWITCH WITH DIMMER 12 BULB 25 AMP HEAVY DUTY ELECTRONIC FLASHER NO MISCELLANEOUS GAUGES		

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: N0225EA WHITE ELITE SS  
 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS  
 PAINT

**Certification / Compliance**

CANADA CMVSS CERTIFICATION, EXCEPT  
 SALES CABS AND GLIDER KITS

**T O T A L V E H I C L E S U M M A R Y**

**Weight Summary**

	<b>Weight Front</b>	<b>Weight Rear</b>	<b>Total Weight</b>
Factory Weight <sup>+</sup>	10814 lbs	8592 lbs	19406 lbs
<hr/>			
Total Weight <sup>+</sup>	10814 lbs	8592 lbs	19406 lbs

(+) Weights shown are estimates only.  
If weight is critical, contact Customer Application Engineering.