

3497

<u>DBCCode</u>	<u>OTCONotes</u>	<u>Description</u>	<u>Value</u>	
AA1-003	D	TRUCK/TRAILER CONFIGURATION		
AA6-003	D	DOMICILED, CANADA (OTHER THAN QUEBEC)		
A85-011	D	CONSTRUCTION SERVICE		
AA3-004	D	END DUMP BODY		
AA2-023	D	FRAMED END DUMP (NON-TRANSFER) TRAILER		
AH6-001	D	SINGLE (1) TRAILER		
AA5-006	D	TERRAIN/DUTY: 10% (SOME) OF THE TIME, IN		
	D	TRANSIT, IS SPENT ON NON-PAVED ROADS		
AB5-003	D	MAINTAINED GRAVEL OR CRUSHED ROCK - MOST		
	D	SEVERE IN-TRANSIT (BETWEEN SITES) ROAD		
	D	SURFACE		
AB1-008	D	MAXIMUM 8% EXPECTED GRADE		
AA4-010	D	DIRT/SAND/ROCK COMMODITY		
A84-	D	CONSTRUCTION BUSINESS SEGMENT		
1CO				
A66-99D	D	EXPECTED FRONT AXLE(S) LOAD	20000	LBS
A68-99D	D	EXPECTED REAR DRIVE AXLE(S) LOAD	40000	LBS
A67-99D	D	EXPECTED PUSHER AXLE(S) LOAD	20000	LBS
A63-99D	D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY	80000	LBS
A70-99D	D	EXPECTED GROSS COMBINATION WEIGHT	88000	LBS
AC8-	S			
99D		CALC'D BACK OF CAB TO REAR SUSP C/L (CA)	188.386	IN
AL8-99D	S	CALC'D CAB TO BODY (INCL 2" CLEARANCE)	15.78	IN
A88-99D	S	EXPECTED TRUCK BODY LENGTH	0	IN
AL4-99D	S	CALC'D FRAME LENGTH BACK OF CAB	254.331	IN
AL6-99D	S	CALC'D BODY AFT OF EOF (+=BODY OVERHANG)	-	IN
			238.551	
AM1-	S			
99D	002	CALC'D OVERALL LENGTH AT BODY OR EOF	376.126	IN
AC3-	S			
99D		CALC'D VEHICLE SPEED @ GOVERNED ENG RPM	83.669	MPH
A89-99D	H002	BRAKING-EXPECTED CAB TO BODY CLEARANCE	16	IN
	002	EXHAUST REQUIRED SPACE		
AK2-	S			
99D		BRAKING-MAX CG OF LOAD ABOVE FRAME @GVWR	32	IN
AM3-	S			
99D		CALC'D FRAME HEIGHT @ REAR SUSP-EXP LOAD	40.759	IN

AR1-99D	S 005	CAL'D FRAME HT AT FRONT SUSP-UNLADEN	43.573	IN
AM2-99D	S	CALC'D FRAME HEIGHT @ REAR SUSP-UNLADEN	42.303	IN
AM0-99D	S	TOP OF FRM TO RR TIRE TOP-UNLD	0.503	IN
ALG-99D	S	CALC'D CAB HEIGHT ABOVE FRAME	71.386	IN
ALJ-99DS		CALC'D CAB HEIGHT ABOVE GROUND; EXP LOAD	112.269	IN
ALH-99D	S 005	CALC'D CAB HEIGHT ABOVE GROUND; UNLADEN	114.344	IN
AF3-2EA	D	WILTSIE TRUCK BODIES		
		MAXIMUM GVW & AXLE SYSTEM CAPACITIES		
A61-99DS		CALC'D MAX CAPACITY FRONT AXLE(S)TOTAL	20000	LBS
A59-99DS		CALC'D MAX CAPACITY DRIVE AXLE(S) TOTAL	46000	LBS
A60-99DS		CALC'D MAX CAP PUSHER/TAG AXLE(S) TOTAL	20000	LBS
A62-99DS		RATED MAXIMUM VEHICLE CAPACITY - GVWR	86000	LBS
		BASE MODEL		
001-177	D	114SD CONVENTIONAL CHASSIS	F 7934	R 6576
004-219	D	2019 MODEL YEAR SPECIFIED		
995-1AE	D	FREIGHTLINER LEVEL II WARRANTY		
002-004	D	SET BACK AXLE - TRUCK	F 480	R -480
019-001	D	TRAILER TOWING PROVISION AT END OF FRAME	F 10	R 10
	D	FOR TRUCK		
003-001	D	LH PRIMARY STEERING LOCATION		
		ENGINE		
101-2YAD		DETROIT DD13 12.8L 450 HP @ 1625 RPM, 19		
	D	00 GOV RPM, 1650 LB/FT @ 975 RPM		
99C-017	D	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/F		
	D	INAL GHG17 CONFIGURATION		
99Z-004	S	VEHICLE IS SUBJECT TO EPA GHG14/GHG17, D		
	S	OES NOT HAVE REGULATORY VEHICLE SPEED LI		
	S	MITER (VSL) OR AUTOMATIC ENGINE SHUTDOWN		
	S	(AES)		
99D-011	D	2008 CARB EMISSION CERTIFICATION - CLEAN		
	D	IDLE (INCLUDES 6X4 INCH LABEL ON LOWER		
	D	FORWARD CORNER OF DRIVER DOOR)		
992-001	S	50 STATE EMISSIONS CERTIFICATION		
28F-007	D	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC		
	D	OVER THE ROAD ACTIVE REGENERATION AND DA		
	D	SH MOUNTED SINGLE REGENERATION REQUEST/I		
	D	NHIBIT SWITCH		
79A-065	D	65 MPH ROAD SPEED LIMIT		

79B-000	D	CRUISE CONTROL SPEED LIMIT SAME AS ROAD
	D	SPEED LIMIT
79C-998	D	NO DRIVER FUEL ECONOMY INCENTIVE
79D-998	D	NO PROGRESSIVE SHIFTING
79E-998	D	NO LOW RANGE TORQUE PROTECT
79F-998	D	NO FLEET MANAGEMENT
79G-998	D	NO IDLE SHUTDOWN CONFIGURATION
79J-998	D	NO PTO SHUTDOWN CONFIGURATION
79K-005	D	PTO MODE ENGINE RPM LIMIT - 900 RPM
79L-998	D	PTO MODE THROTTLE OVERRIDE DISABLED
79M-002	D	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE
	D	APPLIED OR PARK BRAKE NOT APPLIED
79N-998	D	NO PTO MODE CLUTCH OVERRIDE
79P-001	D	PTO RPM WITH CRUISE SET SWITCH - 600 RPM
79Q-001	D	PTO RPM WITH CRUISE RESUME SWITCH - 600
	D	RPM
79R-998	D	NO PTO MODE COOLING FAN
79S-001	D	PTO MODE CANCEL VEHICLE SPEED - 5 MPH
79T-001	D	PTO MODE RPM INCREMENT - 25 RPM
79U-007	D	PTO GOVERNOR RAMP RATE - 250 RPM PER SEC
	D	OND
79V-001	D	ENABLE REGENERATION IN PTO MODE
79W-001	D	ONE REMOTE PTO SPEED
79X-005	D	REMOTE PTO SPEED 1 SETTING - 900 RPM
79Y-998	D	NO PTO 2 SET SPEED
79Z-998	D	NO PTO 3 SET SPEED
80A-998	D	NO ALTERNATE ROAD SPEED LIMIT
80B-998	D	NO CHECK ENGINE LIGHT ON OVERSPEED
80C-998	D	NO ENGINE BRAKE WITH CRUISE CONTROL
80D-001	D	SOFT CRUISE CONTROL ENABLED
80E-998	D	NO ENGINE FAN WITH RETARDER
80F-998	D	NO MAINTENANCE MONITOR
80G-001	D	PTO MINIMUM RPM - 600
80H-998	D	NO ACCELERATION MANAGEMENT
80J-998	D	NO REGEN INHIBIT SPEED THRESHOLD
80R-000	S	DRIVELINE TORQUE PROTECTION - ENABLED
84E-000	D	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DT
	D	NA AND ALLISON, THIS DEFINED BY ENGINE A
	D	ND VOCATIONAL USAGE
84F-000	D	SECONDARY SHIFT SCHEDULE RECOMMENDED BY
	D	DTNA AND ALLISON, THIS DEFINED BY ENGINE
	D	AND VOCATIONAL USAGE
84G-000	D	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA
	D	AND ALLISON, THIS DEFINED BY ENGINE AND

D VOCATIONAL USAGE
 84H-000 D SECONDARY SHIFT SPEED RECOMMENDED BY DTN
 D A AND ALLISON, THIS DEFINED BY ENGINE AN
 D D VOCATIONAL USAGE
 84J-000 S ENGINE BRAKE RANGE PRESELECT RECOMMENDED
 S BY DTNA AND ALLISON, THIS DEFINED BY EN

 S GINE AND VOCATIONAL USAGE
 84K-000 S ENGINE BRAKE RANGE ALTERNATE PRESELECT R
 S ECOMMENDED BY DTNA AND ALLISON, THIS DEF
 S INED BY ENGINE AND VOCATIONAL USAGE
 84L-000 D DYNAMIC SHIFT SENSING AND ACCELERATION R
 D ATE MANAGEMENT RECOMMENDED BY DTNA AND A
 D LLISON, THIS DEFINED VOCATIONAL USAGE
 84N-000 S NEUTRAL AT STOP - DISABLED, FUELSENSE -
 S DISABLED
 85E-998 D TCU-MAX PTO ENGINE SPEED ENGAGEMENT NOT
 D CONFIGURED
 85F-998 D TCU-MAX PTO ENGINE SPEED OPERATION NOT C
 D ONFIGURED
 85G-998 D TCU-MAXIMUM PTO OUTPUT SPEED ENGAGEMENT
 D NOT CONFIGURED
 85H-998 D TCU-MAXIMUM PTO OUTPUT SPEED OPERATION N
 D OT CONFIGURED
 ENGINE EQUIPMENT
 13E-001 D STANDARD OIL PAN
 105-001 D ENGINE MOUNTED OIL CHECK AND FILL
 104-998 D NO ENGINE OIL DRAIN/SAMPLE
 133-004 S ONE PIECE VALVE COVER
 014-1B5 D SIDE OF HOOD AIR INTAKE WITH DONALDSON H
 D IGH CAPACITY AIR CLEANER WITH SAFETY ELE
 D MENT, FIREWALL MOUNTED
 124-1DJ D DR 12V 160 AMP 36-SI BRUSHLESS QUADRAMOU
 D NT PAD ALTERNATOR WITH REMOTE BATTERY VO
 D LT SENSE
 292-071 D (3) ALLIANCE MODEL 1231XOE, GROUP 31, 12
 D VOLT MAINTENANCE FREE 3375 CCA THREADED
 D STUD BATTERIES
 290-017 D BATTERY BOX FRAME MOUNTED
 281-001 D STANDARD BATTERY JUMPERS

 282-001 D SINGLE BATTERY BOX FRAME MOUNTED LH SIDE
 D UNDER CAB
 291-017 D WIRE GROUND RETURN FOR BATTERY CABLES WI

D	TH ADDITIONAL FRAME GROUND RETURN			
289-001 D	NON-POLISHED BATTERY BOX COVER			
33M-998 D	NO AUXILIARY POWER DISTRIBUTION MANAGEMEN			
D	T			
293-058 D	POSITIVE LOAD DISCONNECT WITH CAB MOUNTE	F	8	
D	D CONTROL SWITCH MOUNTED OUTBOARD DRIVER			
D	SEAT			
295-998 D	NO JUMPSTART POST			
180-998 D	NO CLUTCH			
183-998 D	NO CLUTCH BRAKE			
181-998 D	NO CLUTCH RELEASE BEARING LUBE			
182-998 D	NO CLUTCH RELEASE			
107-044 D	BW MODEL BA-921 19.0 CFM SINGLE CYLINDER			
D	AIR COMPRESSOR WITH SAFETY VALVE			
152-041 D	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROT			
D	ECTION SYSTEM			
128-002 D	JACOBS COMPRESSION BRAKE			
016-1C2 D	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL	F	30	R 25
D	AFTERTREATMENT SYSTEM ASSEMBLY WITH RH			
D	B-PILLAR MOUNTED VERTICAL TAILPIPE			
239-038 D	11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) E			
D	XHAUST SYSTEM HEIGHT			
233-017 D	STANDARD CURVE BRIGHT UPPER STACK(S)			
237-1CR D	RH CURVED VERTICAL TAILPIPE B-PILLAR MOU			
D	NTED ROUTED FROM STEP			
23U-002 D	13 GALLON DIESEL EXHAUST FLUID TANK			
43W-001 S	STANDARD DIESEL EXHAUST FLUID SYSTEM COO			
S	LANT PLUMBING			
30N-003 D	100 PERCENT DIESEL EXHAUST FLUID FILL			
23Z-001 D	POLISHED ALUMINUM DIAMOND PLATE DIESEL E	F	15	R 5
D	XHAUST FLUID TANK COVER			
43X-002 D	LH MEDIUM DUTY STANDARD DIESEL EXHAUST F			
D	LUID TANK LOCATION			
23Y-001 D	STANDARD DIESEL EXHAUST FLUID PUMP MOUNT			
D	ING			
43Y-001 D	STANDARD DIESEL EXHAUST FLUID TANK CAP			
242-001 D	STAINLESS STEEL AFTERTREATMENT DEVICE/MU			
D	FFLER/TAILPIPE SHIELD			
273-036 D	BORG WARNER (KYSOR) REAR AIR ON/OFF ENGI			
D	NE FAN CLUTCH			
276-001 D	AUTOMATIC FAN CONTROL WITHOUT DASH SWITC			
D	H, NON ENGINE MOUNTED			
110-068 D	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/			
D	FUEL WATER SEPARATOR WITH WATER-IN-FUEL			

	D	INDICATOR		
118-001	D	FULL FLOW OIL FILTER		
120-998	D	NO COOLANT FILTER		
266-057	D	1500 SQUARE INCH ALUMINUM RADIATOR		
267-003	S	RADIATOR MOUNTED SURGE TANK		
103-040	D	ANTIFREEZE TO -60F, OAT (NITRITE AND SIL		
	D	ICATE FREE) EXTENDED LIFE COOLANT		
171-007	D	GATES BLUE STRIPE COOLANT HOSES OR EQUIV		
	D	ALENT		
172-001	D	CONSTANT TENSION HOSE CLAMPS FOR COOLANT		
	D	HOSES		
270-023	D	HDEP FIXED RATIO COOLANT PUMP AND RADIAT		
	D	OR DRAIN VALVE		
168-998	D	NO RADIATOR/OIL PAN GUARD		
360-998	D	NO FRONT ENGINE PTO		
361-998	D	NO REAR ENGINE PTO		
138-005	D	PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK	F	4
	D	HEATER		
141-998	D	NO COOLANT HEATER - GAS/DSL		
166-998	D	NO OIL PREHEATER		
140-022	D	CHROME ENGINE HEATER RECEPTACLE MOUNTED		
	D	UNDER LH DOOR		
132-998	D	NO AIR INTAKE WARMER		
155-074	D	DELCO 12V MOD 3.175-39MT+ OCP STARTER WI	F	-35
	D	TH THERMAL PROTECTION AND INTEGRATED MAG		
	D	NETIC SWITCH		
		TRANSMISSION & EQUIPMENT		
342-1M3	D	ALLISON 4500 RDS AUTOMATIC TRANSMISSION	F	260 R 100
	D	WITH PTO PROVISION		
352-998	D	NO AUXILIARY TRANSMISSION		
343-324	D	ALLISON VOCATIONAL PACKAGE 175 - AVAILAB		
	D	LE ON 3000/4000 PRODUCT FAMILIES WITH VO		
	D	CATIONAL MODEL RDS		
84B-012	D	ALLISON VOCATIONAL RATING FOR ON/OFF HIG		
	D	HWAY APPLICATIONS AVAILABLE WITH ALL PRO		
	D	DUCT FAMILIES		
84C-023	D	PRIMARY MODE GEARS, LOWEST GEAR 1, START		
	D	GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3		
	D	000/4000 PRODUCT FAMILIES ONLY		
84D-023	D	SECONDARY MODE GEARS, LOWEST GEAR 1, STA		
	D	RT GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR		
	D	3000/4000 PRODUCT FAMILIES ONLY		
97G-004	D	TRANSMISSION PROGNOSTICS - ENABLED 2013		
345-003	D	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DA		

D	SH MOUNTED	
347-998	D NO CLUTCH HOUSING MATERIAL	
370-011	D WATER TO OIL TRANSMISSION COOLER, FRAME	
	D MOUNTED	
346-003	D TRANSMISSION OIL CHECK AND FILL WITH ELE	
	D CTRONIC OIL LEVEL CHECK	
368-998	D NO EXTERNAL TRANSMISSION OIL FILTER	F -2
341-018	D MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSI	
	D ON DRAIN, AXLE(S) FILL AND DRAIN	
84T-000	S DISABLE - NEUTRAL RANGE ASSIST	
84U-000	D DRIVER SWITCH INPUT - DEFAULT - NO SWITC	
	D HES	
84V-001	S DIRECTION CHANGE ENABLED WITH MULTIPLEXE	
	S D SERVICE BRAKES - ALLISON 5TH GEN TRANS	
	S MISSIONS	
84W-001	S AUXILIARY FUNCTION RANGE INHIBIT WITH MU	
	S LTIPIEXED SERVICE BRAKES - ALLISON 5TH G	
	S EN TRANSMISSIONS	
85D-001	S SINGLE INPUT AUTOMATIC NEUTRAL WITH SELE	
	S CTOR OVERRIDE WITH MULTIPLEXED PARK BRAK	
	S E - ALLISON 5TH GEN TRANSMISSIONS	
353-022	D VEHICLE INTERFACE WIRING CONNECTOR WITHO	
	D UT BLUNT CUTS, AT BACK OF CAB	
34C-001	D ELECTRONIC TRANSMISSION CUSTOMER ACCESS	
	D CONNECTOR FIREWALL MOUNTED	
362-035	D CUSTOMER INSTALLED CHELSEA 277 SERIES PT	
	D O	
363-001	D PTO MOUNTING, LH SIDE OF MAIN TRANSMISSI	
	D ON	
375-998	D NO AUXILIARY OIL COOLER	
373-998	D NO TRANSFER CASE	
376-998	D NO SHIFT CONTROL, TRANSFER CASE	
371-998	D NO AUX TRANS/TRANSFER CASE MTD POWER	
	D TAKEOFF	
35T-001	D SYNTHETIC TRANSMISSION FLUID (TES-295 CO	
	D MPLIANT)	
385-998	D NO MAIN DRIVELINE HARDWARE	
	D FRONT AXLE, SUSPENSION & EQUIPMENT	
400-1AC	D MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.	F 260
	D 74 INCH DROP SINGLE FRONT AXLE	
398-998	D NO FRONT AXLE RATIO	
389-998	D NO FRONT AXLE DRIVESHAFT	

402-030	D	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT	F	10	
	D	BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
403-002	D	NON-ASBESTOS FRONT BRAKE LINING			
419-023	D	CONMET CAST IRON FRONT BRAKE DRUMS			
427-001	D	FRONT BRAKE DUST SHIELDS	F	5	
409-006	D	FRONT OIL SEALS			
408-001	D	VENTED FRONT HUB CAPS WITH WINDOW, CENTE			
	D	R AND SIDE PLUGS - OIL			
416-022	D	STANDARD SPINDLE NUTS FOR ALL AXLES			
404-1B2	S	WABCO LONGSTROKE FRONT BRAKE CHAMBERS			
405-002	D	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS			
406-001	D	STANDARD KING PIN BUSHINGS			
536-055	D	TRW THP-60 POWER STEERING WITH RCH45 AUX	F	130	
	D	ILIARY GEAR			
537-005	S	STEEL STEERING SHAFT			
539-003	D	POWER STEERING PUMP			
534-003	D	4 QUART POWER STEERING RESERVOIR			
533-001	D	OIL/AIR POWER STEERING COOLER			
40T-002	D	SYNTHETIC 75W-90 FRONT AXLE LUBE			
620-025	D	20,000# TAPERLEAF FRONT SUSPENSION	F	200	
619-005	D	MAINTENANCE FREE RUBBER BUSHINGS - FRONT			
	D	SUSPENSION			
629-998	D	NO FRONT SWAYBAR			
410-001	D	FRONT SHOCK ABSORBERS			
		REAR AXLE, SUSPENSION & EQUIPMENT			
420-059	D	RT-46-164P 46,000# R-SERIES TANDEM REAR			R 580
	D	AXLE			
421-410	D	4.10 REAR AXLE RATIO			
424-001	D	IRON REAR AXLE CARRIER WITH STANDARD AXL			
	D	E HOUSING			
42T-001	D	STANDARD REAR AXLE BREATHER(S)			
382-998	D	NO (#1) DRIVELINE			
386-078	D	MXL 18N MERITOR EXTENDED LUBE MAIN DRIVE	F	100	R 100
	D	LINE WITH FULL ROUND YOKES			
388-073	D	MXL 17T MERITOR EXTENDED LUBE INTERAXLE			
	D	DRIVELINE WITH HALF ROUND YOKES			
452-006	D	DRIVER CONTROLLED TRACTION DIFFERENTIAL			R 40
	D	- BOTH TANDEM REAR AXLES			
878-022	D	(1) INTERAXLE LOCK VALVE, (1) DRIVER CON			
	D	TROLLED DIFFERENTIAL LOCK FORWARD-REAR A			
	D	XLE VALVE AND (1) REAR-REAR AXLE VALVE			
87A-002	D	BUZZER AND BLINKING LAMP WITH EACH INTER			
	D	AXLE LOCK SWITCH, INTERAXLE UNLOCK DEFAU			
	D	LT WITH IGNITION OFF			

87B-005	D	BUZZER AND BLINKING LAMP WITH EACH MODE	
	D	SWITCH, DIFFERENTIAL UNLOCK WITH IGNITIO	
	D	N OFF, ACTIVE <5 MPH	
423-019	D	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REA	
	D	R BRAKES, DOUBLE ANCHOR, FABRICATED SHOE	
	D	S	
433-002	D	NON-ASBESTOS REAR BRAKE LINING	
434-005	D	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE	
	D	OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT	
	D	BRACKETS	
451-023	D	CONMET CAST IRON REAR BRAKE DRUMS	
425-002	D	REAR BRAKE DUST SHIELDS	R 10
440-006	D	REAR OIL SEALS	
426-112	D	WABCO TRISTOP-D LONGSTROKE 30/36 2-DRIVE	
	D	AXLE SPRING PARKING CHAMBERS	
428-002	D	MERITOR AUTOMATIC REAR SLACK ADJUSTERS	
41T-002	D	SYNTHETIC 75W-90 REAR AXLE LUBE	
622-108	D	AIRLINER 46,000# REAR SUSPENSION WITH CH	R 420
	D	AIN CLEARANCE	
034-998	D	NO REAR SUSPENSION PACKAGE	
621-007	D	AIRLINER HIGH POSITION RIDE HEIGHT	
431-004	D	WELDED AXLE SEATS SUPPLIED ON REAR AXLE	
624-025	D	55 INCH AXLE SPACING	
628-998	D	NO SUSPENSION BEAMS	
888-048	D	MANUAL DUMP VALVE FOR AIR SUSPENSION WIT	
	D	H GAUGE	
87D-006	D	INDICATOR LIGHT FOR EACH REAR SUSPENSION	
	D	CONTROL SWITCH	
910-001	D	SINGLE AIR REAR SUSPENSION LEVELING VALV	
	D	E	
623-002	D	TRANSVERSE CONTROL RODS	
630-998	D	NO REAR SUSPENSION STABILIZER	
625-998	D	NO REAR SUSPENSION OPTIONS	
439-005	D	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM	
	D) (AIR RIDE SUSPENSION)	
035-1A1	D	HENDRICKSON SC20 COMPOSILITE 20,000# AIR	F 925 R 930
	D	LIFT STEERABLE PUSHER SUSPENSION, 16.5X	
	D	6 BRAKES AND FL1 AXLE	
443-1D0	D	HENDRICKSON SC20/SCO20 20,000# FL1 STEER	
	D	ABLE 16.5X6 BRAKE INTEGRAL PUSHER AXLE	
456-1AF	D	HENDRICKSON 16.5X6 CAST SPIDER CAM PUSHE	
	D	R/TAG BRAKES, DOUBLE ANCHOR, FABRICATED	
	D	SHOES	
457-002	D	NON-ASBESTOS PUSHER/TAG BRAKE LINING	

448-023	D	CONMET CAST IRON PUSHER/TAG BRAKE DRUMS	
429-001	D	PUSHER/TAG BRAKE DUST SHIELDS	
442-016	D	PUSHER/TAG OIL SEALS	
444-001	D	VENTED PUSHER/TAG HUB CAPS WITH WINDOW,	
	D	CENTER AND SIDE PLUGS - OIL	
445-075	D	HALDEX LONGSTROKE PUSHER/TAG AXLE SERVIC	
	D	E CHAMBERS	
458-003	D	HALDEX AUTOMATIC PUSHER/TAG SLACK ADJUST	
	D	ERS	
626-1E1	D	HENDRICKSON SC20 COMPOSILITE 20,000# STE	
	D	ERABLE AIR LIFT PUSHER SUSPENSION	
627-023	D	101 INCH AXLE SPACING PUSHER/TAG	
874-015	D	(1) DASH VALVE AND (1) GAUGE FOR SINGLE	
	D	LIFT AXLE	
896-014	D	AIR PIPING FOR (1) LIFT/NON-LIFT AXLE WI	
	D	TH REGULATOR CHASSIS MOUNTED	
87F-005	D	REVERSE LIFT AXLE WIRING WITH LAST STATE	
	D	RETENTION WITH IGNITION OFF	
		BRAKE SYSTEM	
490-100	D	WABCO 4S/4M ABS WITHOUT TRACTION CONTROL	
871-001	D	REINFORCED NYLON, FABRIC BRAID AND WIRE	
	D	BRAID CHASSIS AIR LINES	
46E-001	S	STANDARD AIR MANAGEMENT UNIT	
904-001	D	FIBER BRAID PARKING BRAKE HOSE	
412-001	D	STANDARD BRAKE SYSTEM VALVES	
46D-002	D	STANDARD AIR SYSTEM PRESSURE PROTECTION	
	D	SYSTEM	
413-002	D	STD U.S. FRONT BRAKE VALVE	
432-021	D	(2) 3-4.5 PSI RELAY VALVES, ONE FOR TAND	
	D	EM AXLE AND ONE FOR PUSHER/TAG	
480-009	D	BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	F 20
483-003	D	BENDIX OIL COALESCING FILTER FOR AIR DRY	
	D	ER	
479-003	D	AIR DRYER MOUNTED INBOARD ON LH RAIL	
460-058	D	STEEL AIR TANKS MOUNTED AFT INSIDE AND/O	
	D	R BELOW FRAME JUST FORWARD OF REAR SUSPE	
	D	NSION	
46A-998	D	NO AUXILIARY AIR TANK	
607-998	D	CHASSIS CONFIGURATION - NONE	
477-004	D	PULL CABLES ON ALL AIR RESERVOIR(S)	
485-998	D	NO EXTERNAL CHARGING GLADHAND	
481-998	D	NO TRAILER AIR HOSE	
476-998	D	NO AIR HOSE HANGER	

914-025	D	AIR CONNECTIONS TO END OF FRAME WITH GLA				
	D	D HANDS FOR TRUCK AND DUST COVERS				
919-998	D	NO OPTIONAL CHASSIS AIR SYSTEM PIPING,				
	D	VALVES, OR AIR UNLOADER SYSTEM				
484-998	D	NO TRAILER CABLE AND GLAD HANDS STORAGE				
296-028	D	SWITCH AND INDICATOR LIGHT FOR PRIMARY R				
	D	ECEPTACLE CENTER PIN, LABELED TRLR-AUX,				
	D	WITH STOP SIGNAL PREWIRE PACKAGE				
297-001	D	SAE J560 7-WAY PRIMARY TRAILER CABLE REC				
	D	EPTACLE MOUNTED END OF FRAME				
335-004	D	UPGRADED CHASSIS MULTIPLEXING UNIT				
87P-001	S	CAB AUXILIARY POWER CABLE	F	5		
331-001	D	SUPPLEMENTAL J560 7-WAY RECEPTACLE LOCAT				
	D	ED WITH PRIMARY RECEPTACLE				
303-998	H002	NO ADDITIONAL TRAILER CABLE RECEPTACLE				
	002	7-WAY RECEPTACLE EOF (IAS) FOR TRACTOR/T				
		RAILER CONFIGURATION				
334-998	H002	NO ADDITIONAL SUPPLEMENTAL 7-WAY				
	H	TRAILER CABLE RECEPTACLE				
	002	THERE IS NO DESIGN COVERAGE FOR A MODULE				
		334 RECEPTACLE WITHOUT A MODULE 303 REC				
		EPTACLE				
310-998	D	NO TRAILER ELECTRICAL CABLE				
		FRAME & WHEELBASE				
545-645	D	6450MM (254 INCH) WHEELBASE				
546-1B2	D	1/2X3.64X11-7/8 INCH STEEL FRAME (12.7MM	F	850	R	100
	D	X301.6MM/0.5X11.88 INCH) 120KSI				
547-001	D	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME	F	255	R	444
	D	REINFORCEMENT				
548-998	D	NO OUTER FRAME REINFORCEMENT				
549-998	D	NO FRONT FRAME EXTENSION				
552-033	D	1675MM (66 INCH) REAR FRAME OVERHANG				
AB8-99D	S	CALC'D FRAME SLOPE @ FRT/RR SUSP RATINGS	-0.235		%	
553-001	D	SQUARE END OF FRAME				
550-001	D	FRONT CLOSING CROSSMEMBER				
559-001	D	STANDARD WEIGHT ENGINE CROSSMEMBER				
562-001	D	STANDARD MIDSHIP #1 CROSSMEMBER(S)				
565-002	D	HEAVY DUTY SUSPENSION CROSSMEMBER			R	30
572-001	D	STANDARD REARMOST CROSSMEMBER				
AL5-99DS	002	CALC'D BUMPER TO REAR TOWING C/M FACE	376.126		IN	
587-998	D	NO REAR TOWING DEVICE				
588-998	D	NO REAR TOW DEVICE HEIGHT				

CHASSIS EQUIPMENT

674-998	D	NO LH OR RH BACK OF CAB ACCESS		
592-998	D	NO DECK PLATE		
556-1F0	H002	14 INCH CHROMED STEEL SEVERE DUTY BUMPER		
	H	WITH CENTER TOW DEVICE		
	002	THE 556-1E9 AND 556-1F0 BUMPERS ARE THE ONLY ONES THAT CAN MOUNT THE 558-063 TOW PIN ON A 114SD. A DIFFERENT BUMPER CAN BE USED IF A DIFFERENT 558 CODE, SUCH AS 558-065, 558-001, 558-033, OR 558-998 IS USED.		
557-002	D	LOOP STEP MOUNTED BELOW BUMPER	F	10
558-063	D	HEAVY DUTY CENTER MOUNTED TOW PIN		
55E-998	D	NO BUMPER MOUNTING BRACKETS		
642-998	D	NO BUMPER/FENDER MOUNTED SIGHT RODS		
574-001	D	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
585-998	D	NO MUDFLAP BRACKETS		
590-998	D	NO REAR MUDFLAPS		
586-024	S	FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS	F	10
	S			
551-002	D	HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS		
583-998	D	NO REAR QUARTER FENDERS		
489-998	D	NO TIRE PRESSURE CONTROL/SENSOR		
794-998	D	NO JACK OR WHEEL WRENCH PROVISION		
795-998	D	NO TOOLS		
605-003	D	LEVEL FRAME RAILS (+/- 1%) WHEN CHASSIS IS LOADED TO FRONT AND REAR SUSPENSION RAIL MOUNTINGS		
	D			
	D			
606-998	D	NO TRUCK BODY		
601-998	D	NO BODY BUILDER DIAGRAMS		
970-998	D	NO BODY TYPE		
		FIFTH WHEEL & EQUIPMENT		
578-998	D	NO FIFTH WHEEL		
577-998	D	NO FIFTH WHEEL LOCATION		
580-998	D	NO ADDITIONAL FIFTH WHEEL DRILLINGS		
582-998	D	NO FIFTH WHEEL LEG HEIGHT		
570-998	D	NO FIFTH WHEEL MOUNTING		
890-998	D	NO FIFTH WHEEL PLUMBING		
579-998	D	NO FIFTH WHEEL RELEASE/INST.		
591-998	D	NO FIFTH WHEEL ADD-ONS		
581-998	D	NO FIFTH WHEEL RAMP		
		FUEL TANK(S) & EQUIPMENT		
206-998	D	NO RH FUEL TANK		
201-998	D	NO RH AUXILIARY FUEL TANK		

204-155	D	90 GALLON/340 LITER ALUMINUM FUEL TANK -	F	15		
	D	LH				
200-998	D	NO LH AUXILIARY FUEL TANK				
230-998	D	NO BETWEEN RAIL FUEL TANK				
203-011	D	60 GALLON ALUMINUM HYDRAULIC RESERVOIR,	F	60	R	55
	D	LH WITH 1-1/4 INCH NPT TOP AND BOTTOM EN				
	D	D FITTINGS				
	002	001 MOUNT HYDRAULIC TANK CENTERED BETWEEN		23	3	
	002	002 LIFT AXLE AND FORWARD DRIVE AXLE		N/C	C	
	002	REF VIN JK7506 AND KD4328				
	QUOTE	ASSIGNED QUOTE JWCD 1801041607				
218-006	D	25 INCH DIAMETER FUEL TANK(S)				
215-006	D	POLISHING OF FUEL/HYDRAULIC TANK(S) WITH				
	D	POLISHED STAINLESS STEEL BANDS				
212-007	D	FUEL TANK(S) FORWARD				
231-998	D	NO FUEL TANK MTG BETWEEN RAILS				
232-998	D	NO ADDITIONAL FUEL PROVIDED				
664-002	D	POLISHED STEP FINISH				
207-998	D	NO FUEL TANK SCREENS				
205-002	D	CHROME FUEL TANK CAP(S)				
220-998	D	NO FUEL HEATER				
122-998	D	NO FUEL/WATER SEPARATOR				
216-020	D	EQUIFLO INBOARD FUEL SYSTEM				
20E-998	D	NO AUXILIARY FUEL SUPPLY AND RETURN PORT				
	D	S				
202-016	D	HIGH TEMPERATURE REINFORCED NYLON FUEL L				
	D	INE				
213-998	D	NO FUEL LINE INSULATION				
221-998	D	NO FUEL COOLER				
20A-003	H003	SINGLE HYDRAULIC TANK FRAME MOUNTED LH S				
	H	IDE BACK OF CAB				
	003	Adding the 20A sales code helps to relie				
		ve confusion when pre-buildshopcall team				
		reviews the specs				
		TIRES				
093-0TB	D	MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL	F	196		
	D	FRONT TIRES				
094-1UX	D	MICHELIN X MULTI D 11R22.5 14 PLY RADIAL			R	192
	D	REAR TIRES				
095-0TB	D	MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL			R	196
	D	PUSHER/TAG TIRES				
510-998	D	NO SPARE TIRE				
		HUBS				
418-060	D	CONMET PRESET PLUS PREMIUM IRON FRONT HU				

	D	BS	
450-060	D	CONMET PRESET PLUS PREMIUM IRON REAR HUB	
	D	S	
449-060	D	CONMET PRESET PLUS PREMIUM IRON PUSHER/TAG HUBS	
	D	WHEELS	
502-091	D	ACCURIDE 29374A 22.5X12.25 10-HUB PILOT	F -8
	D	4.75 INSET 10-HAND ALUMINUM DISC FRONT	
	D	WHEELS	
505-1EF	D	ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS	R -200
	D		
509-034	D	ACCURIDE 29374A 22.5X12.25 10-HUB PILOT	R -6
	D	4.75 INSET 10-HAND ALUMINUM DISC	
	D	PUSHER/TAG WHEELS	
511-998	D	NO SPARE WHEEL	
51A-998	D	NO ADDITIONAL SPARE WHEEL	
524-002	C005	POLISHED FRONT WHEELS; INSIDE AND OUTSIDE	
	C	E	
525-001	D	POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY	
	D		
526-007	C005	POLISHED PUSHER/TAG WHEELS; BOTH SIDES OF OUTER WHEELS ONLY	
	C		
50W-998	D	NO RIM/WHEEL TIRE PRESSURE SENSOR	
498-011	D	NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES	
	D	CAB EXTERIOR	
829-1A2	D	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB	
	D		
682-998	D	NO SLEEPER BOX/SLEEPER CAB	
784-998	D	NO AIR SHIELD OR BRACKETS	
783-998	D	NO SIDE EXTENDERS	
782-998	D	NO FRAME SIDE FAIRINGS	
650-008	D	AIR CAB MOUNTING	
705-998	D	NO MISCELLANEOUS CUSTOM CAB REQUIREMENTS	
648-002	D	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE	
	D	ILLE	
667-004	D	FRONT FENDERS SET-BACK AXLE	
754-017	D	BOLT-ON MOLDED FLEXIBLE FENDER EXTENSION	F 10
	D	S	
678-001	D	LH AND RH GRAB HANDLES	
645-002	D	BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL	
646-042	D	STATIONARY BLACK GRILLE WITH BRIGHT ACCENT	

D	NTS		
65X-003	D	CHROME HOOD MOUNTED AIR INTAKE GRILLE	
644-004	D	FIBERGLASS HOOD	
690-016	D	CAB FLOOR, TOE BOARD AND FIREWALL HEAT S	F 5
	D	HIELD	
727-066	D	DUAL 26 INCH RECTANGULAR POLISHED ALUMIN	F 4
	D	UM AIR HORNS ROOF MOUNTED	
726-001	D	SINGLE ELECTRIC HORN	
728-002	D	DUAL HORN SHIELDS	
657-1CV	D	DOOR LOCKS AND IGNITION SWITCH KEYED THE	
	D	SAME WITH (4) KEYS	
575-001	D	REAR LICENSE PLATE MOUNT END OF FRAME	
327-998	D	NO OTHER LIGHTS	
312-067	D	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT	
	D	BEZELS	
302-047	D	LED AERODYNAMIC MARKER LIGHTS	
315-998	D	NO FOG LIGHTS	
311-012	D	DAYTIME RUNNING LIGHTS - LOW BEAM ONLY	
316-998	D	NO SPOTLIGHTS	
294-042	D	FREIGHTLINER LED FLANGE MOUNTED STOP/TAI	R 5
	D	L/TURN LIGHTS WITH SEPARATE INCANDESCENT	
	D	BACKUP LIGHTS	
300-015	D	STANDARD FRONT TURN SIGNAL LAMPS	
318-998	D	NO UTILITY/ADVERTISING LIGHT	
744-1BMD	D	DUAL WEST COAST BRIGHT FINISH HEATED MIR	
	D	RORS	
797-001	D	DOOR MOUNTED MIRRORS	
796-001	D	102 INCH EQUIPMENT WIDTH	
743-204	D	LH AND RH 8 INCH BRIGHT FINISH CONVEX MI	
	D	RRORS MOUNTED UNDER PRIMARY MIRRORS	
74A-998	D	NO AUXILIARY MIRROR	
74B-998	D	NO AUXILIARY MIRROR	
712-998	D	NO CUSTOM NAMEPLATE	
713-998	D	NO PERMIT PLAQUE	
729-001	D	STANDARD SIDE/REAR REFLECTORS	
73A-998	D	NO REFLECTIVE DEVICES	
677-055	D	RH AFTERTREATMENT SYSTEM CAB ACCESS WITH	
	D	POLISHED DIAMOND PLATE COVER	
27D-998	D	NO ALTERNATING FLASHING HEADLAMP SYSTEM	
275-998	D	NO EMERGENCY WARNING SIRENS	
764-010	D	COMPOSITE EXTERIOR SUN VISOR	F 10
768-043	D	63X14 INCH TINTED REAR WINDOW	
661-003	D	TINTED DOOR GLASS LH AND RH WITH TINTED	
	D	NON-OPERATING WING WINDOWS	

654-027	D	RH AND LH ELECTRIC POWERED WINDOWS, PASS	F	4
	D	ENGER SWITCHES ON DOOR(S)		
767-998	D	NO SIDE WINDOW		
769-998	D	NO LOWER DOOR WINDOW		
663-013	D	TINTED WINDSHIELD		
659-020	D	2 GALLON WINDSHIELD WASHER RESERVOIR WIT		
	D	H FLUID LEVEL INDICATOR, FRAME MOUNTED		
647-998	D	NO WINTERFRONT		
		CAB INTERIOR		
707-1AK	D	OPAL GRAY VINYL INTERIOR		
055-004	D	INTERIOR CONVENIENCE PACKAGE WITH CB PRO		
	D	VISION		
706-026	D	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL		
	D	INSERT WITH ALUMINUM KICKPLATE LOWER DOO		
	D	R		
708-026	D	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL		
	D	INSERT WITH ALUMINUM KICKPLATE LOWER DOO		
	D	R		
772-006	D	BLACK MATS WITH SINGLE INSULATION		
785-001	D	DASH MOUNTED ASH TRAYS AND LIGHTER		
691-008	D	FORWARD ROOF MOUNTED CONSOLE WITH UPPER		
	D	STORAGE COMPARTMENTS WITHOUT NETTING		
694-998	D	NO INTERIOR GLOVE BOX/CAB FLOOR STORAGE		
696-998	D	NO REAR FLOOR STORAGE		
693-998	D	NO INTERIOR DOOR STORAGE		
826-998	D	NO LOWER BUNK		
666-998	D	NO BUNK RESTRAINT		
738-998	D	NO CLOCK		
742-007	D	(2) CUP HOLDERS LH AND RH DASH		
680-007	D	GRAY/CHARCOAL WING DASH		
860-004	D	SMART SWITCH EXPANSION MODULE		
33A-998	D	NO WARNING LIGHT SWITCHES		
720-002	D	2-1/2 LB. FIRE EXTINGUISHER	F	5
71T-998	D	NO SMOKE/GAS DETECTOR		
714-001	D	FIRST AID KIT	F	2
700-002	D	HEATER, DEFROSTER AND AIR CONDITIONER		
701-008	D	STANDARD HVAC DUCTING WITH SNOW SHIELD F		
	D	OR FRESH AIR INTAKE		
703-005	D	MAIN HVAC CONTROLS WITH RECIRCULATION SW		
	D	ITCH		
689-998	D	NO AUXILIARY HVAC UNIT		
170-045	D	STANDARD HEATER PLUMBING WITH BALL SHUTO		
	D	FF VALVES AT SUPPLY LINES ONLY		
130-033	D	DENSO HEAVY DUTY AIR CONDITIONER COMPRES		

	D	SOR		
702-002	D	BINARY CONTROL, R-134A		
739-034	D	PREMIUM INSULATION		
285-013	D	SOLID-STATE CIRCUIT PROTECTION AND FUSES		
96R-002	S	STANDARD ELECTRICAL PROTECTIVE COATING,		
	S	WHITE LITHIUM GREASE ON BATTERY TERMINAL		
	S	S AND RED ENAMEL PAINT IN ENGINE COMPART		
	S	MENT AND ON CHASSIS CONNECTIONS		
280-007	D	12V NEGATIVE GROUND ELECTRICAL SYSTEM		
324-011	D	DOME DOOR ACTIVATED LH AND RH, DUAL READ		
	D	ING LIGHTS, FORWARD CAB ROOF		
655-005	D	LH AND RH ELECTRIC DOOR LOCKS		
740-998	D	NO MATTRESS		
284-023	D	(1) 12 VOLT POWER SUPPLY IN DASH		
710-998	D	NO CAB PRIVACY CURTAIN		
722-002	D	TRIANGULAR REFLECTORS WITHOUT FLARES	F	10
756-1D9	D	PREMIUM HIGH BACK AIR SUSPENSION DRIVER	F	70
	D	SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRAT		
	D	ED CUSHION EXTENSION, FORWARD AND REAR C		
	D	USHION TILT, ADJUSTABLE SHOCK ABSORBER		
760-1DC	D	BASIC HIGH BACK NON SUSPENSION PASSENGER		
	D	SEAT		
762-998	D	NO REAR PASSENGER SEAT		
757-998	D	NO SEAT SKIRT(S)		
759-007	D	DUAL DRIVER SEAT ARMRESTS, NO PASSENGER	F	4
	D	SEAT ARMRESTS		
711-004	D	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
699-998	D	NO SEAT OPTIONS		
758-025	D	GRAY MORDURA CLOTH DRIVER SEAT COVER		
761-025	D	GRAY MORDURA CLOTH PASSENGER SEAT COVER		
755-998	D	NO REAR PASSENGER SEAT COVERS		
763-101	D	BLACK SEAT BELTS		
532-002	D	ADJUSTABLE TILT AND TELESCOPING STEERING	F	10
	D	COLUMN		
540-016	D	18 INCH (450MM) LEATHER WRAPPED STEERING		
	D	WHEEL		
765-002	D	DRIVER AND PASSENGER INTERIOR SUN VISORS		
		CONTROLS & INSTRUMENTS		
870-001	D	BLACK GAUGE BEZELS		
732-003	D	WOODGRAIN DRIVER INSTRUMENT PANEL		
734-003	D	WOODGRAIN CENTER INSTRUMENT PANEL		
68J-998	D	NO SWITCH BLANK - INSTRUMENT PANEL		

486-001 D LOW AIR PRESSURE INDICATOR LIGHT AND AUD
 D IBLE ALARM
 838-998 D NO AIR APPLICATION GAUGE
 840-002 D 2 INCH PRIMARY AND SECONDARY AIR PRESSUR
 D E GAUGES
 198-002 D INTAKE MOUNTED AIR RESTRICTION INDICATOR
 D WITH GRADUATIONS
 721-001 D 97 DB BACKUP ALARM
 149-017 D ELECTRONIC CRUISE CONTROL WITH SWITCHES
 D ON AUXILIARY GAUGE PANEL (B DASH PANEL)
 156-007 D KEY OPERATED IGNITION SWITCH AND INTEGRA
 D L START POSITION; 4 POSITION OFF/RUN/STA
 D RT/ACCESSORY
 157-998 D NO REMOTE START
 811-042 D ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS,
 D 28 LED WARNING LAMPS AND DATA LINKED
 160-038 D HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE
 D CONNECTOR LOCATED BELOW LH DASH
 844-001 D 2 INCH ELECTRIC FUEL GAUGE
 845-011 D FUEL FILTER RESTRICTION INDICATOR
 148-085 D EMISSIONS LIMITED IDLE ADJUST
 163-998 D NO ENGINE OPT/RPM CONTROLS WIRING
 87L-998 D NO REMOTE ENGINE CONTROL-ENABLE
 33U-998 D NO CUSTOMER DEFINED WIRING FUNCTION
 866-998 D NO AXLE TEMPERATURE GAUGE
 856-001 D ELECTRICAL ENGINE COOLANT TEMPERATURE GA
 D UGE
 854-998 D NO ENGINE OIL TEMPERATURE GAUGE

 864-001 D 2 INCH TRANSMISSION OIL TEMPERATURE GAUG
 D E
 867-998 D NO OUTSIDE AIR TEMPERATURE GAUGE
 830-017 D ENGINE AND TRIP HOUR METERS INTEGRAL WIT
 D HIN DRIVER DISPLAY
 438-998 D NO HUBODOMETER
 372-051 D CUSTOMER FURNISHED AND INSTALLED PTO CON
 D TROLS
 73H-998 D NO CAMERA/VIDEO/IMAGING SYSTEM
 49B-998 D NO VEHICLE STABILITY ADVISOR OR CONTROL
 852-002 D ELECTRIC ENGINE OIL PRESSURE GAUGE
 679-001 D OVERHEAD INSTRUMENT PANEL
 35M-998 D NO WRG-BDY MULTIPLEX EXPNSN UNIT
 786-998 D NO POSITIONING/LOCATING SYSTEM
 78C-998 D NO DIGITAL SATELLITE AUDIO RECEIVER ANTE
 D NNA

746-1B4	D	AM/FM/WB WORLD TUNER RADIO WITH CD PLAYE	F	10
	D	R, BLUETOOTH, IPOD INTERFACE, USB AND AU		
	D	XILIARY INPUTS, J1939		
747-001	D	DASH MOUNTED RADIO		
74D-998	D	NO RADIO/SPEAKER WIRING		
750-002	D	(2) RADIO SPEAKERS IN CAB		
753-998	D	NO AM/FM RADIO ANTENNA		
748-014	D	COBRA 29NW LTD CLASSIC FACTORY INSTALLED	F	5
	D	CB RADIO		
749-001	D	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION		
752-018	D	MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNT	F	4
	D	ED ANTENNA SYSTEM		
810-028	D	ELECTRONIC KPH SPEEDOMETER WITH SECONDAR		
	D	Y MPH SCALE, WITHOUT ODOMETER		
817-001	D	STANDARD VEHICLE SPEED SENSOR		
812-001	D	ELECTRONIC 3000 RPM TACHOMETER		
813-1B4	D	VT-HU CONNECTIVITY PLATFORM HARDWARE		
8D1-002	D	2 YEARS DETROIT CONNECT BASE PACKAGE (VI		
	D	RTUAL TECHNICIAN, DETROIT CONNECT PORTAL		
	D	ACCESS)FOR VT-HU CONNECTIVITY PLATFORM		
8Z1-998	D	NO ZONAR SERVICES SELECTED		
80K-998	D	NO SHUTDOWN OVERRIDE		
80L-998	D	NO REGEN SYSTEM TAILORING		
80M-998	S	NO ALTERNATE PTO SPEED		
80N-998	D	NO REDUCED ENGINE SPEED ON VSS FAILURE		
80P-998	S	NO FLEET SPEC FOR PARAMETERIZATION		
80Q-998	S	NO VEHICLE SPEED LIMIT - GHG		
162-002	D	IGNITION SWITCH CONTROLLED ENGINE STOP		
885-998	D	NO CONTROLS-FIRE PUMP		
329-015	D	ONE ON/OFF ROCKER SWITCH IN THE DASH WIT		
	D	H INDICATOR LIGHT AND WIRE ROUTED TO CHA		
	D	SSIS AT BACK OF CAB, LABEL OPT		
81Y-001	D	PRE-TRIP LAMP INSPECTION, ALL OUTPUTS FL		
	D	ASH, WITH SMART SWITCH		
44R-998	D	NO ON/OFF LATCHING SMARTPLEX SWITCH		
44S-998	D	NO ON/OFF MOMENTARY SMARTPLEX SWITCH		
44T-998	D	NO ON/OFF/ON LATCHING SMARTPLEX SWITCH		
44U-998	D	NO ON/OFF/ON MOMENTARY SMARTPLEX SWITCH		
44V-998	D	NO PRE-DEFINED SMARTPLEX INDICATOR LAMPS		
44W-998	D	NO UNDEFINED INDICATOR LAMPS		
264-998	D	NO CONTROLS-SIREN/AIR HORN		
482-001	D	BW TRACTOR PROTECTION VALVE		
883-001	D	TRAILER HAND CONTROL BRAKE VALVE		
836-015	D	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DR		

D IVER DISPLAY
 660-025 D SINGLE ELECTRIC WINDSHIELD WIPER MOTOR W
 D ITH DELAY PROGRAMMED TO SLOWEST SPEED WI
 D TH PARK BRAKE SET
 304-003 D MARKER LIGHT/HEADLIGHT SWITCH WITH SEPAR
 D ATE INTERRUPTER FOR CLEARANCE LIGHTS

 882-004 D TWO VALVE PARKING BRAKE SYSTEM WITH WARN
 D ING INDICATOR
 299-013 D SELF CANCELING TURN SIGNAL SWITCH WITH D
 D IMMER, WASHER/WIPER AND HAZARD IN HANDLE
 298-048 D INTEGRAL ELECTRONIC TURN SIGNAL FLASHER
 D WITH STOP LAMPS OVERRIDING HAZARD LAMPS
 869-998 D NO MISCELLANEOUS GAUGES
 PAINT
 065-000 D PAINT: ONE SOLID COLOR
 980-513 D CAB COLOR A: L0183EB
 D BRIGHT SILVER MET ELITE BC
 986-020 D BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
 D PAINT
 98K-998 D NO FUEL TANK CABINET PAINT
 962-998 D PAINT-FRT WHEEL COLOR: NONE
 966-998 D PAINT-RR WHEEL COLOR: NONE
 96E-998 D NO PUSHER/TAG WHEEL PAINT
 96F-998 D NO SPARE WHEEL PAINT
 964-998 D NO BUMPER PAINT
 976-995 D SUNVISOR PAINTED SAME AS CAB COLOR A
 963-003 D STANDARD E COAT/UNDERCOATING
 ADDITIONAL SPECIFICATIONS
 998-998 D DEALER ACCEPTS RESPONSIBILITY FOR IN-SER
 D VICE PDI INSPECTION
 958-998 D NO INSPECTION-LABOR ONLY
 99B-998 D NO MODIFICATION CENTER SHIPPING INSTRUCT
 D IONS
 82N-998 D NO SHIPPING PROTECTION
 999-034 H002 DEALER ADVISED AND ACCEPTS TERMS OF PIL
 H #395; SPEED OF LOADED VEHICLE MUST BE LI
 H MITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXL
 H E IS RAISED
 996-002 D CANADA CMVSS CERTIFICATION, EXCEPT SALES
 WAI-983 EW4: DD13 VOC \$0 DED 7 YEARS/400,000 MIL
 ES/644,000 KM FULL COVERAGE. FEX APPLIES

 WAK- ALLISON 4500 RDS SERIES TRANSMISSION EXT
 140 ENDED WARRANTY, 5 YEARS/UNLIMITED MILES

WAG-
010

P28-1AC 001

FEX

TOWING: 1 YEAR/UNLIMITED MILES/KM EXTEND

ED TOWING COVERAGE \$550 CAP FEX APPLIES

AIR CONDITIONING TAX