

## S P E C I F I C A T I O N P R O P O S A L

| Data Code                    | Description   | Weight<br>Front | Weight<br>Rear |
|------------------------------|---|-----------------|----------------|
| <b>Price Level</b>           |   |                 |                |
| PRL-20W                      | WESTERN STAR PRL-20W (EFF:04/30/19)   |                 |                |
| <b>Data Version</b>          |   |                 |                |
| DRL-010                      | SPECPRO21 DATA RELEASE VER 010  |                 |                |
| <b>Vehicle Configuration</b> |   |                 |                |
| 001-424                      | WESTERN STAR 4900SA CHASSIS   | 9,674           | 6,696          |
| 004-221                      | 2021 MODEL YEAR SPECIFIED   |                 |                |
| 002-004                      | SET BACK AXLE - TRUCK   | -10             |                |
| 019-001                      | TRAILER TOWING PROVISION AT END OF<br>FRAME FOR TRUCK   | 10              | 10             |
| 003-001                      | LH PRIMARY STEERING LOCATION  |                 |                |
| <b>General Service</b>       |   |                 |                |
| AA1-003                      | TRUCK/TRAILER CONFIGURATION   |                 |                |
| AA6-003                      | DOMICILED, CANADA (OTHER THAN QUEBEC)   |                 |                |
| RCE-00V                      | VARIABLE CANADIAN EXCHANGE  |                 |                |
| A85-011                      | CONSTRUCTION SERVICE  |                 |                |
| A84-1CO                      | CONSTRUCTION BUSINESS SEGMENT   |                 |                |
| AA4-010                      | DIRT/SAND/ROCK COMMODITY  |                 |                |
| AA5-002                      | TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN<br>TRANSIT, IS SPENT ON PAVED ROADS                    |                 |                |
| AB1-008                      | MAXIMUM 8% EXPECTED GRADE   |                 |                |
| AB5-001                      | SMOOTH CONCRETE OR ASPHALT PAVEMENT -<br>MOST SEVERE IN-TRANSIT (BETWEEN SITES)<br>ROAD SURFACE |                 |                |
| 995-1A5                      | WESTERN STAR VOCATIONAL WARRANTY  |                 |                |
| A66-99D                      | EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs   |                 |                |
| A68-99D                      | EXPECTED REAR DRIVE AXLE(S) LOAD :<br>40000.0 lbs   |                 |                |
| A67-99D                      | EXPECTED PUSHER AXLE(S) LOAD : 20000.0 lbs  |                 |                |
| A63-99D                      | EXPECTED GROSS VEHICLE WEIGHT CAPACITY<br>: 80000.0 lbs   |                 |                |
| A70-99D                      | EXPECTED GROSS COMBINATION WEIGHT :<br>88000.0 lbs  |                 |                |
| <b>Truck Service</b>         |   |                 |                |

| Data Code | Description  | Weight Front | Weight Rear |
|-----------|--|--------------|-------------|
| AA3-004   | END DUMP BODY  |              |             |
| AF4-99D   | EXPECTED EMPTY BODY WEIGHT : 4300.0 lbs                              |              |             |
| A88-99D   | EXPECTED TRUCK BODY LENGTH : 0.0 ft                                  |              |             |
| AE2-99D   | EXPECTED TRUCK BODY WIDTH : 96.0 in                                  |              |             |
| AF6-99D   | EXP EMPTY BODY CG LOC FROM BODY<br>FRT(A89) : 5.9 ft                 |              |             |
| A89-99D   | BRAKING-EXPECTED CAB TO BODY<br>CLEARANCE : 7.72 in                  |              |             |
| AF7-99D   | EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE<br>FRAME "XX" INCHES : 32.0 in |              |             |

### Engine

101-2XW DETROIT DD15 14.8L 505 HP @ 1625 RPM, 1900  
 GOV RPM, 1750 LB/FT @ 975 RPM

### Electronic Parameters

79A-065 65 MPH ROAD SPEED LIMIT  
 79B-000 CRUISE CONTROL SPEED LIMIT SAME AS ROAD  
 SPEED LIMIT  
 79D-035 1600 RPM HARD AND SOFT ENGINE LIMIT FOR  
 PROGRESSIVE SHIFTING  
 79G-006 5 MINUTES IDLE SHUTDOWN WITH CLUTCH  
 AND SERVICE BRAKE OVERRIDE  
 79K-005 PTO MODE ENGINE RPM LIMIT - 900 RPM  
 79M-002 PTO MODE BRAKE OVERRIDE - SERVICE  
 BRAKE APPLIED OR PARK BRAKE NOT APPLIED  
 79N-001 PTO MODE CLUTCH OVERRIDE - CLUTCH  
 ENABLED  
 79P-001 PTO RPM WITH CRUISE SET SWITCH - 600 RPM  
 79Q-001 PTO RPM WITH CRUISE RESUME SWITCH - 600  
 RPM  
 79S-001 PTO MODE CANCEL VEHICLE SPEED - 5 MPH  
 79T-001 PTO MODE RPM INCREMENT - 25 RPM  
 79U-007 PTO GOVERNOR RAMP RATE - 250 RPM PER  
 SECOND  
 79W-001 ONE REMOTE PTO SPEED  
 79X-005 PTO SPEED 1 SETTING - 900 RPM  
 80P-998 NO FLEET SPEC FOR PARAMETERIZATION  
 80D-001 SOFT CRUISE CONTROL ENABLED  
 80G-001 PTO MINIMUM RPM - 600

### Engine Equipment

99C-017 2016-2019 ONBOARD DIAGNOSTICS/2010  
 EPA/CARB/FINAL GHG17 CONFIGURATION

| Data Code | Description   | Weight Front | Weight Rear |
|-----------|---|--------------|-------------|
| 99D-011   | 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)        |              |             |
| 13E-001   | STANDARD OIL PAN  |              |             |
| 105-001   | ENGINE MOUNTED OIL CHECK AND FILL   |              |             |
| 133-004   | ONE PIECE VALVE COVER   |              |             |
| 014-041   | DUAL POLISHED STAINLESS STEEL 13 INCH DONALDSON COWL MOUNTED 1-STAGE AIR CLEANERS WITH POLISHED STAINLESS STEEL BANDS | 40           |             |
| 124-1D7   | DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE  |              |             |
| 292-217   | (4) DTNA GENUINE, AGM STARTING AND CYCLING, MIN 2920CCA, 760RC, THREADED STUD BATTERIES                               | 60           | 20          |
| 290-1AC   | PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE OF CAB   | -100         | -35         |
| 282-013   | BATTERY BOX MOUNTED UNDER PASSENGER SEAT  |              |             |
| 291-017   | WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN   |              |             |
| 289-006   | PLASTIC BATTERY BOX COVER   |              |             |
| 293-058   | POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT                                 | 8            |             |
| 180-101   | EATON ADVANTAGE 15-1/2 INCH MANUALLY ADJUSTED CLUTCH  |              |             |
| 183-008   | TORQUE LIMITING CLUTCH BRAKE  |              |             |
| 181-004   | ZERK FITTINGS WITH EXTENSION HOSES AT CLUTCH RELEASE BEARING AND X-SHAFT  |              |             |
| 18B-003   | CUSTOMER REQUESTS MINIMUM CLUTCH TORQUE RATING OF 2050 LB-FT  |              |             |
| 107-044   | BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE   |              |             |
| 131-013   | AIR COMPRESSOR DISCHARGE LINE   |              |             |
| 152-041   | ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM   |              |             |
| 128-002   | JACOBS COMPRESSION BRAKE  |              |             |
| 016-1C4   | RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH DUAL CAB MOUNTED VERTICAL TAILPIPES     | 55           | 33          |

| Data Code | Description  | Weight<br>Front | Weight<br>Rear |
|-----------|--|-----------------|----------------|
| 28F-007   | ENGINE AFTERTREATMENT DEVICE,<br>AUTOMATIC OVER THE ROAD ACTIVE<br>REGENERATION AND DASH MOUNTED SINGLE<br>REGENERATION REQUEST/INHIBIT SWITCH |                 |                |
| 239-044   | 12 FOOT 00 INCH (144 INCH+0/-5.9 INCH)<br>EXHAUST SYSTEM HEIGHT  |                 |                |
| 233-019   | STANDARD CURVE BRIGHT UPPER STACK(S)<br>AND ELBOW(S)   |                 |                |
| 237-1CK   | DUAL CURVED VERTICAL TAILPIPES B-PILLAR<br>MOUNTED   |                 |                |
| 23U-003   | 23 GALLON DIESEL EXHAUST FLUID TANK  |                 |                |
| 30N-003   | 100 PERCENT DIESEL EXHAUST FLUID FILL  |                 |                |
| 23Z-001   | POLISHED ALUMINUM DIAMOND PLATE DIESEL<br>EXHAUST FLUID TANK COVER   |                 |                |
| 43X-001   | LH HEAVY DUTY STANDARD DIESEL EXHAUST<br>FLUID TANK LOCATION   |                 |                |
| 43Y-001   | STANDARD DIESEL EXHAUST FLUID TANK CAP   |                 |                |
| 242-021   | OVAL PERFORATED DUAL STAINLESS STEEL<br>MUFFLER/TAILOPIPE SHIELDS WITH WESTERN<br>STAR LOGO  |                 |                |
| 273-036   | BORG WARNER (KYSOR) REAR AIR ON/OFF<br>ENGINE FAN CLUTCH   |                 |                |
| 276-002   | AUTOMATIC FAN CONTROL WITH DASH<br>SWITCH AND INDICATOR LIGHT, NON ENGINE<br>MOUNTED   |                 |                |
| 110-068   | DDC SUPPLIED ENGINE MOUNTED FUEL<br>FILTER/FUEL WATER SEPARATOR WITH<br>WATER-IN-FUEL INDICATOR  |                 |                |
| 118-001   | FULL FLOW OIL FILTER   |                 |                |
| 266-057   | 1500 SQUARE INCH ALUMINUM RADIATOR   | -130            |                |
| 267-006   | MOUNTING FOR FIREWALL MOUNTED SURGE<br>TANK  |                 |                |
| 103-037   | ANTIFREEZE TO -60F, ETHYLENE GLYCOL PRE-<br>CHARGED SCA HEAVY DUTY COOLANT   |                 |                |
| 171-007   | GATES BLUE STRIPE COOLANT HOSES OR<br>EQUIVALENT   |                 |                |
| 172-010   | CONSTANT TENSION HOSE CLAMPS FOR<br>COOLANT HOSES AND AIR INTAKE SYSTEM  |                 |                |
| 270-023   | HDEP FIXED RATIO COOLANT PUMP AND<br>RADIATOR DRAIN VALVE  |                 |                |
| 138-005   | PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK<br>HEATER  | 4               |                |
| 166-005   | PHILLIPS-TEMRO 300 WATT/115 VOLT OIL<br>PREHEATER  | 4               |                |

| Data Code                       | Description   | Weight Front | Weight Rear |
|---------------------------------|---|--------------|-------------|
| 140-041                         | CHROME COMMON BLOCK AND OIL PAN HEATER RECEPTACLE MOUNTED UNDER LH DOOR         |              |             |
| 155-075                         | MITSUBISHI 12V MOD 3.175-DP60 STARTER WITH INTEGRATED MAGNETIC SWITCH           |              |             |
| 109-007                         | CAST IRON FRONT AND REAR ENGINE SUPPORTS  |              |             |
| <b>Transmission</b>             |   |              |             |
| 342-1BP                         | EATON FULLER RTLO-18918B TRANSMISSION   | 90           | 40          |
| <b>Transmission Equipment</b>   |   |              |             |
| 348-002                         | POLISHED STAINLESS STEEL TRANSMISSION BOOT RING                                 |              |             |
| 347-001                         | CAST IRON CLUTCH HOUSING  |              |             |
| 362-802                         | CUSTOMER INSTALLED CHELSEA 442 SERIES PTO                                       |              |             |
| 363-003                         | PTO MOUNTING, BOTTOM OF MAIN TRANSMISSION                                       |              |             |
| 345-001                         | PAINTED SHIFT LEVER, SOLID LINKAGE  |              |             |
| 370-015                         | WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK                          |              |             |
| 35T-003                         | SYNTHETIC TRANSMISSION LUBE   |              |             |
| <b>Front Axle and Equipment</b> |   |              |             |
| 400-1AC                         | MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE          | 240          |             |
| 402-030                         | MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES | 10           |             |
| 403-002                         | NON-ASBESTOS FRONT BRAKE LINING   |              |             |
| 419-023                         | CONMET CAST IRON FRONT BRAKE DRUMS  |              |             |
| 427-001                         | FRONT BRAKE DUST SHIELDS  | 5            |             |
| 409-006                         | FRONT OIL SEALS   |              |             |
| 408-001                         | VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL                  |              |             |
| 416-022                         | STANDARD SPINDLE NUTS FOR ALL AXLES   |              |             |
| 405-003                         | HALDEX AUTOMATIC FRONT SLACK ADJUSTERS  |              |             |
| 536-1A3                         | TRW TAS-85 POWER STEERING WITH RCH45 AUXILIARY GEAR                             | 175          |             |
| 539-003                         | POWER STEERING PUMP   |              |             |
| 534-003                         | 4 QUART POWER STEERING RESERVOIR  | 5            |             |
| 533-001                         | OIL/AIR POWER STEERING COOLER   | 5            |             |
| 40T-002                         | SYNTHETIC 75W-90 FRONT AXLE LUBE  |              |             |

| Data Code                      | Description  | Weight Front | Weight Rear |
|--------------------------------|--|--------------|-------------|
| <b>Front Suspension</b>        |  |              |             |
| 620-068                        | 23,000# FLAT LEAF FRONT SUSPENSION   | 350          |             |
| 619-002                        | THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION   |              |             |
| 62G-001                        | ALUMINUM SPACER BLOCKS FOR FRONT SUSPENSIONS   |              |             |
| 62H-001                        | CAST IRON SHACKLED FRONT AND REAR SPRING BRACKETS FOR FRONT SUSPENSION   |              |             |
| 410-001                        | FRONT SHOCK ABSORBERS  |              |             |
| <b>Rear Axle and Equipment</b> |  |              |             |
| 420-059                        | RT-46-164P 46,000# R-SERIES TANDEM REAR AXLE   |              | 580         |
| 421-391                        | 3.91 REAR AXLE RATIO   |              |             |
| 424-001                        | IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING  |              |             |
| 386-019                        | SPL250HD XL DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES   | 80           | 80          |
| 388-012                        | SPL170 XL DANA SPICER INTERAXLE DRIVELINE WITH HALF ROUND YOKES  |              | 10          |
| 452-006                        | DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES   |              | 30          |
| 878-044                        | (1) INTERAXLE LOCK VALVE SUPPLIES (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AXLE VALVE AND (1) REAR-REAR AXLE VALVE |              |             |
| 87A-005                        | INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH  |              |             |
| 87B-008                        | INDICATOR LIGHT FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH  |              |             |
| 423-019                        | MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES  |              |             |
| 433-002                        | NON-ASBESTOS REAR BRAKE LINING   |              |             |
| 434-003                        | STANDARD BRAKE CHAMBER LOCATION  |              |             |
| 451-023                        | CONMET CAST IRON REAR BRAKE DRUMS  |              |             |
| 425-002                        | REAR BRAKE DUST SHIELDS  |              | 10          |
| 440-006                        | REAR OIL SEALS   |              |             |
| 426-1B3                        | BENDIX EVERSURE LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS   |              |             |
| 428-003                        | HALDEX AUTOMATIC REAR SLACK ADJUSTERS  |              |             |
| 41T-002                        | SYNTHETIC 75W-90 REAR AXLE LUBE  |              |             |
| 42T-001                        | STANDARD REAR AXLE BREATHER(S)   |              |             |
| <b>Rear Suspension</b>         |  |              |             |

| Data Code | Description   | Weight Front | Weight Rear |
|-----------|---|--------------|-------------|
| 622-1M5   | NEWAY ADZ 246 46,000# REAR AIR SUSPENSION                           |              | 300         |
| 621-012   | NEWAY AD/ARD/ADZ; HENDRICKSON HAS; REYCO 240AR, 10.00" RIDE HEIGHT  |              |             |
| 431-001   | STANDARD AXLE SEATS IN AXLE CLAMP GROUP                             |              |             |
| 624-010   | 60 INCH AXLE SPACING  |              |             |
| 888-003   | MANUAL DUMP VALVE FOR AIR SUSPENSION WITH INDICATOR LIGHT AND GAUGE |              |             |
| 910-004   | DUAL AIR REAR SUSPENSION LEVELING VALVES                            |              |             |
| 623-006   | FORE/AFT AND TRANSVERSE CONTROL RODS                                |              |             |
| 439-005   | REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)     |              |             |

### Pusher / Tag Equipment

|         |   |     |     |
|---------|---|-----|-----|
| 035-1A1 | HENDRICKSON SC20 COMPOSILITE 20,000# AIR LIFT STEERABLE PUSHER SUSPENSION, 16.5X6 BRAKES AND FL1 AXLE | 925 | 925 |
| 443-1D0 | HENDRICKSON SC20/SCO20 20,000# FL1 STEERABLE 16.5X6 BRAKE INTEGRAL PUSHER AXLE                        |     |     |
| 874-004 | (1) DASH SWITCH, (1) GAUGE AND (1) AIR PRESSURE REGULATOR INSIDE CAB                                  |     |     |
| 87F-005 | REVERSE LIFT AXLE WIRING WITH LAST STATE RETENTION WITH IGNITION OFF                                  |     |     |
| 896-007 | AIR PIPING FOR LIFTABLE PUSHER/TAG AXLE, CONTROLS MOUNTED INSIDE CAB                                  |     |     |
| 456-1AF | HENDRICKSON 16.5X6 CAST SPIDER CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED SHOES                 |     |     |
| 457-002 | NON-ASBESTOS PUSHER/TAG BRAKE LINING  |     |     |
| 448-023 | CONMET CAST IRON PUSHER/TAG BRAKE DRUMS   |     |     |
| 429-001 | PUSHER/TAG BRAKE DUST SHIELDS   |     | 5   |
| 442-016 | PUSHER/TAG OIL SEALS  |     |     |
| 444-002 | STEMCO ALUMINUM VENTED PUSHER/TAG HUB CA PS WITH WINDOW AND CENTER PLUG, OIL                          |     |     |
| 445-075 | HALDEX LONGSTROKE PUSHER/TAG AXLE SERVICE CHAMBERS  |     |     |
| 458-003 | HALDEX AUTOMATIC PUSHER/TAG SLACK ADJUSTERS   |     |     |
| 626-1E1 | HENDRICKSON SC20 COMPOSILITE 20,000# STEERABLE AIR LIFT PUSHER SUSPENSION                             |     |     |
| 627-023 | 101 INCH AXLE SPACING PUSHER/TAG  |     |     |

| Data Code                    | Description  | Weight Front | Weight Rear |
|------------------------------|--|--------------|-------------|
| <b>Brake System</b>          |  |              |             |
| 490-100                      | WABCO 4S/4M ABS  |              |             |
| 871-023                      | REINFORCED NYLON AIR LINES   |              |             |
| 904-001                      | FIBER BRAID PARKING BRAKE HOSE   |              |             |
| 412-001                      | STANDARD BRAKE SYSTEM VALVES   |              |             |
| 432-013                      | COMBO-ABS/SERVICE BRAKE VALVE WITH 5.5 PSI CRACK PRESSURE  |              |             |
| 480-009                      | BW AD-9 BRAKE LINE AIR DRYER WITH HEATER   | 20           |             |
| 483-003                      | BENDIX OIL COALESCING FILTER FOR AIR DRYER   |              |             |
| 479-003                      | AIR DRYER MOUNTED INBOARD ON LH RAIL   |              |             |
| 460-008                      | STEEL AIR BRAKE RESERVOIRS MOUNTED INSIDE RAIL   |              |             |
| 477-004                      | PULL CABLES ON ALL AIR RESERVOIR(S)  |              |             |
| <b>Trailer Connections</b>   |  |              |             |
| 481-998                      | NO TRAILER AIR HOSE  | -10          |             |
| 914-001                      | AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS                       | 5            | 5           |
| 296-010                      | PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION |              |             |
| 297-001                      | SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME                               |              |             |
| 308-003                      | SUPPLEMENTAL RECEPTACLE WIRING FOR THIRD AXLE LIFT   |              |             |
| 331-001                      | SUPPLEMENTAL J560 7-WAY RECEPTACLE LOCATED WITH PRIMARY RECEPTACLE                                 |              |             |
| 310-998                      | NO TRAILER ELECTRICAL CABLE  | -10          |             |
| <b>Wheelbase &amp; Frame</b> |  |              |             |
| 545-677                      | 6775MM (267 INCH) WHEELBASE  |              |             |
| 546-503                      | 3/8X3-7/8X11-5/8 INCH DOUBLE CHANNEL 120KSI STEEL FRAME (3/8 INCH OUTER AND 1/4 INCH INNER)        | 1,070        | 670         |
| 552-018                      | 1625MM (64 INCH) REAR FRAME OVERHANG   |              |             |
| 55W-006                      | FRAME OVERHANG RANGE: 61 INCH TO 70 INCH   | -30          | 140         |
| AC8-99D                      | CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 193.73 in   |              |             |
| AE8-99D                      | CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 186.01 in                           |              |             |
| AE4-99D                      | CALC'D FRAME LENGTH - OVERALL : 368.41   |              |             |



| Data Code                | Description  | Weight Front | Weight Rear |
|--------------------------|--|--------------|-------------|
| ZF1-99D                  | FRAME HEIGHT TOP FRONT UNLADEN : 0.0 in  |              |             |
| ZF2-99D                  | FRAME HEIGHT TOP FRONT LADEN : 32.23 in  |              |             |
| ZF3-99D                  | FRAME HEIGHT TOP REAR UNLADEN : 42.48 in   |              |             |
| ZF4-99D                  | FRAME HEIGHT TOP REAR LADEN : 41.12 in   |              |             |
| FSS-0LH                  | CALCULATED FRAME SPACE LH SIDE : -50.19 in   |              |             |
| FSS-0RH                  | CALCULATED FRAME SPACE RH SIDE : -8.51 in  |              |             |
| AM6-99D                  | CALC'D SPACE AVAILABLE FOR DECKPLATE : 194.0 in  |              |             |
| 560-001                  | UNDERSLUNG CROSSMEMBER   | 40           |             |
| 553-001                  | SQUARE END OF FRAME  |              |             |
| 550-002                  | HEAVY DUTY FRONT CLOSING CROSSMEMBER   | 120          |             |
| 561-009                  | EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION BACK OF TRANSMISSION CROSSMEMBER    |              |             |
| 562-022                  | EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION MIDSHIP #1 CROSSMEMBER              | 5            | 5           |
| 572-043                  | 1/4 INCH STEEL C-CHANNEL CROSSMEMBER WITHOUT A-FRAME, NON-TOWING                         |              | 20          |
| 56C-001                  | STANDARD WEIGHT REAR SUSPENSION FORWARD CROSSMEMBER                                      |              |             |
| 565-001                  | STANDARD SUSPENSION CROSSMEMBER  |              |             |
| 568-006                  | EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION REAR MOUNTED SUSPENSION CROSSMEMBER |              |             |
| <b>Chassis Equipment</b> |  |              |             |
| 674-998                  | NO LH OR RH BACK OF CAB ACCESS   | -5           | -5          |
| 592-998                  | NO DECK PLATE  | -5           | -5          |
| 556-1AX                  | 14 INCH TAPERED SWEPTBACK CHROMED STEEL BUMPER   |              |             |
| 558-026                  | NON REMOVABLE CENTERED FRONT TOW PIN FOR HIGHWAY OR CONSTRUCTION BUMPER                  |              |             |
| 574-001                  | BUMPER MOUNTING FOR SINGLE LICENSE PLATE   |              |             |
| 585-998                  | NO MUDFLAP BRACKETS  |              | -25         |
| 590-998                  | NO REAR MUDFLAPS   |              | -15         |
| 586-024                  | FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS  | 10           |             |
| 551-007                  | GRADE 8 THREADED HEX HEADED FRAME FASTENERS  |              |             |
| 44Z-001                  | EXTERIOR HARNESSSES WRAPPED IN CONDUIT   |              |             |
| 82R-998                  | NO PDI INSTALLED CHASSIS STEPS   |              |             |

| Data Code          | Description   | Weight Front | Weight Rear |
|--------------------|---|--------------|-------------|
| <b>Fifth Wheel</b> |   |              |             |
| 578-998            | NO FIFTH WHEEL  | -30          | -480        |
| <b>Fuel Tanks</b>  |   |              |             |
| 206-154            | 80 GALLON/302 LITER ALUMINUM FUEL TANK - RH                             | 110          | 45          |
| 204-154            | 80 GALLON/302 LITER ALUMINUM FUEL TANK - LH                             | -10          |             |
| 203-061            | 80 GALLON/302 LITER ALUMINUM HYDRAULIC RESERVOIR, LH WITH FITTINGS      | 85           | 80          |
| 218-006            | 25 INCH DIAMETER FUEL TANK(S)   |              |             |
| 215-006            | POLISHING OF FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS |              |             |
| 212-008            | FUEL TANK(S) AFT  |              |             |
| 67N-002            | FULL LENGTH POLISHED HYDRAULIC TANK STEPS                               |              |             |
| 20A-002            | SINGLE HYDRAULIC TANK FRAME MOUNTED LH SIDE UNDER CAB                   |              |             |
| 664-002            | POLISHED STEP FINISH  |              |             |
| 211-001            | FUEL TANK COMPRESSION BRACE   | 30           |             |
| 205-002            | CHROME FUEL TANK CAP(S)   |              |             |
| 216-020            | EQUIFLO INBOARD FUEL SYSTEM   |              |             |
| 202-016            | HIGH TEMPERATURE REINFORCED NYLON FUEL LINE                             |              |             |
| 221-998            | NO FUEL COOLER  |              |             |
| 847-002            | IN TANK FUEL LEVEL SENDER(S)  |              |             |
| <b>Tires</b>       |   |              |             |
| 093-0TB            | MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL FRONT TIRES                    | 196          |             |
| 094-0GK            | MICHELIN XDN2 11R22.5 14 PLY RADIAL REAR TIRES                          |              | 144         |
| 095-0TB            | MICHELIN XZY-3 425/65R22.5 20 PLY RADIAL PUSHER/TAG TIRES               |              | 196         |
| <b>Hubs</b>        |   |              |             |
| 418-060            | CONMET PRESET PLUS PREMIUM IRON FRONT HUBS                              | 60           |             |
| 450-060            | CONMET PRESET PLUS PREMIUM IRON REAR HUBS                               |              | 60          |
| 449-060            | CONMET PRESET PLUS PREMIUM IRON PUSHER/TAG HUBS                         |              |             |
| <b>Wheels</b>      |   |              |             |

| Data Code | Description   | Weight Front | Weight Rear |
|-----------|---|--------------|-------------|
| 502-1H5   | ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS      | -8           |             |
| 505-1EF   | ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS                           |              | 104         |
| 509-1H5   | ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC PUSHER/TAG WHEELS |              | -8          |
| 524-022   | POLISHED DISC SIDE FRONT WHEELS WITH DURA-BRIGHT FINISH   |              |             |
| 525-023   | POLISHED OUTER (DISHED SIDE) REAR WHEELS WITH OUTER ONLY DURA-BRIGHT FINISH                     |              |             |
| 526-022   | POLISHED SINGLES (DISC SIDE) PUSHER/TAG WHEELS WITH DURA-BRIGHT FINISH                          |              |             |
| 50T-998   | NO FRONT AXLE WHEEL/HUB COVER   |              |             |
| 496-011   | FRONT WHEEL MOUNTING NUTS   |              |             |
| 497-011   | REAR WHEEL MOUNTING NUTS  |              |             |

### Cab Exterior

|         |   |     |  |
|---------|---|-----|--|
| 829-1AB | 123 INCH BBC STEEL CONVENTIONAL CAB   |     |  |
| 82A-008 | WESTERN STAR STAINLESS STEEL CAB SKIRT  |     |  |
| 650-044 | AIR CAB MOUNTS WITH CHECK VALVE   | -30 |  |
| 705-007 | STAINLESS STEEL SILL PLATES   | 5   |  |
| 648-002 | NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE  |     |  |
| 667-022 | LARGE PROFILE FRONT FENDER  |     |  |
| 754-007 | 2-3/4 INCH FENDER EXTENSIONS  | 10  |  |
| 678-034 | LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERTS AND RH INTERIOR GRAB HANDLE MOUNTED TO A POST |     |  |
| 645-004 | STAINLESS STEEL RADIATOR SHELL/HOOD BEZEL WITH STYLIZED TILT HOOD HANDLE                          |     |  |
| 646-002 | RADIATOR MOUNTED GRILLE   |     |  |
| 640-008 | GALVANEAELED STEEL SEVERE SERVICE CAB   | 50  |  |
| 644-045 | SUPER VISIBILITY HOOD WITH CAB MOUNTED QUARTER FENDERS  |     |  |
| 643-002 | HEAVY DUTY HOOD MOUNTING  |     |  |
| 727-012 | DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS  | 4   |  |
| 726-001 | SINGLE ELECTRIC HORN  |     |  |
| 728-002 | DUAL HORN SHIELDS   |     |  |
| 657-1AF | DOORS AND IGNITION KEYED THE SAME (3 KEYS)  |     |  |

| Data Code | Description  | Weight Front | Weight Rear |
|-----------|--|--------------|-------------|
| 312-003   | DUAL RECTANGULAR HALOGEN HEADLIGHTS  |              |             |
| 302-022   | LED MARKER LAMPS   |              |             |
| 305-024   | LED ACCENT LIGHTS ON INTAKE BRACKET AND LOWER EDGE OF CAB  | 10           |             |
| 314-023   | PERLUX CLEAR ROADLIGHTS RECESSED IN BUMPER WITH ROCK GUARDS  | 6            |             |
| 315-808   | WIRING AND SWITCH ONLY FOR CUSTOMER FURNISHED FOG LIGHTS   |              |             |
| 311-003   | DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH   |              |             |
| 294-032   | FLUSH MOUNTED STOP/TAIL/BACKUP LIGHTS MOUNTED BELOW REAR MOST CROSSMEMBER  |              |             |
| 300-045   | LED SQUARE CHROME FENDER MOUNTED FRONT TURN SIGNALS  |              |             |
| 31K-1A1   | (2) CHROME INCANDESCENT UTILITY LIGHTS WITH STAINLESS STEEL ANTI-GLARE SHIELDS MOUNTED ON MIRROR ARMS                          | 6            |             |
| 31J-001   | (1) SWITCH WITH INDICATOR AND WIRING FOR CUSTOMER FURNISHED UTILITY LAMP MOUNTED BACK OF CAB/SLEEPER WITH 10 FOOT COILED CABLE |              |             |
| 744-1E0   | DUAL WEST COAST STAINLESS STEEL HEATED MIRRORS WITH LH AND RH REMOTE   |              |             |
| 797-001   | DOOR MOUNTED MIRRORS   |              |             |
| 796-001   | 102 INCH EQUIPMENT WIDTH   |              |             |
| 743-1AA   | LH AND RH SUREPLUS 574 8 INCH BRIGHT FINISH HEATED CONVEX MIRRORS WITH SEPARATE ADJUSTMENT, MOUNTED BELOW MIRROR               |              |             |
| 74A-001   | RH DOWN VIEW MIRROR  |              |             |
| 729-001   | STANDARD SIDE/REAR REFLECTORS  |              |             |
| 677-016   | DUAL LEVEL CAB ENTRY STEPS ON BOTH SIDES   |              |             |
| 764-700   | PDI INSTALL: PLAIN 11" DEEP SLOPED WIDE SUN VISOR FOR NON-STRATOSPHERE SLEEPER CAB   |              |             |
| 768-046   | 17.5X35 INCH TINTED REAR WINDOW  |              |             |
| 661-006   | TINTED DOOR GLASS  |              |             |
| 654-011   | RH AND LH ELECTRIC POWERED WINDOWS   |              |             |
| 769-002   | LOWER RH DOOR WINDOW WITH FRESNEL LENS   | 7            |             |
| 663-014   | 2-PIECE BONDED SOLAR GREEN GLASS WINDSHIELD  |              |             |

| Data Code           | Description   | Weight Front | Weight Rear |
|---------------------|---|--------------|-------------|
| 659-016             | 1.5 GALLON WINDSHIELD WASHER RESERVOIR MOUNTED UNDER CAB WITH REMOTE FILL   |              |             |
| 647-001             | WHITE WINTERFRONT   | 2            |             |
| <b>Cab Interior</b> |   |              |             |
| 707-1D4             | SMOKY MOUNTAIN GRAY VINYL PREMIUM INTERIOR  |              |             |
| 70K-005             | BLACK HARD TRIM   |              |             |
| 706-048             | PREMIUM LEFT HAND DOOR TRIM WITH CHERRY ACCENT  |              |             |
| 708-048             | PREMIUM RIGHT HAND DOOR TRIM WITH CHERRY ACCENT   |              |             |
| 772-007             | BLACK MATS WITH DOUBLE INSULATION   |              |             |
| 785-024             | ASH CUP AND (1) POWER OUTLET  |              |             |
| 691-001             | FORWARD ROOF MOUNTED CONSOLE  |              |             |
| 694-009             | PASSENGER SIDE WING DASH MOUNTED GLOVE BOX WITH LOCKING DOOR  |              |             |
| 693-025             | LH AND RH DOOR MAP POCKETS  |              |             |
| 741-015             | (2) COAT HOOKS ON BACKWALL OF CAB   |              |             |
| 742-998             | NO CUP/THERMOS HOLDER   |              |             |
| 680-033             | BLACK SOFT TOUCH WING DASH WITH DRIVER SIDE COSMETIC UNDER DASH COVER   |              |             |
| 320-004             | STANDARD WIRING   |              |             |
| 720-003             | 5 LB. FIRE EXTINGUISHER   | 10           |             |
| 700-023             | HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT TEMPERATURE CONTROL AND COSMETIC COVER  |              |             |
| 701-002             | HVAC DUCTING WITH MAIN FRESH AIR FILTER   |              |             |
| 170-045             | STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY  |              |             |
| 130-041             | VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR   |              |             |
| 698-001             | RADIATOR MOUNTED AIR CONDITIONER CONDENSER  |              |             |
| 739-002             | ADDITIONAL CAB SIDEWALL INSULATION  | 60           | 10          |
| 285-019             | AUTOMATIC SELF-RESET CIRCUIT BREAKER IN MAIN DASH POWER DISTRIBUTION BOX AND CIRCUIT BREAKER/FUSE IN AUXILIARY POWER DISTRIBUTION BOXES |              |             |
| 324-076             | DOOR ACTIVATED DOME LIGHT, UNDER DASH LIGHT WITH LH AND RH DOOR MOUNTED COURTESY LIGHTS AND LH AND RH READING LIGHTS                    |              |             |
| 655-001             | CAB DOOR LATCHES WITH MANUAL DOOR LOCKS   |              |             |

| Data Code | Description  | Weight Front | Weight Rear |
|-----------|--|--------------|-------------|
| 64C-002   | BRIGHT DOOR HANDLES  |              |             |
| 284-112   | (2) 12 VOLT POWER RECEPTACLES PLATE MOUNTED IN DASH  |              |             |
| 722-028   | TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB  | 10           |             |
| 756-1E1   | ELITE HIGH BACK AIR SUSPENSION DRIVER SEAT WITH HEAT, 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT AND ADJUSTABLE SHOCK | 20           |             |
| 760-038   | NATIONAL 2 MAN TOOL/BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT   | -30          |             |
| 757-001   | BLACK SUSPENSION COVER FOR AIR DRIVER SEAT   | 2            |             |
| 759-007   | DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS  | 4            |             |
| 758-121   | BLACK LAREDO LEATHER DRIVER SEAT COVER   |              |             |
| 761-121   | BLACK LAREDO LEATHER PASSENGER SEAT COVER  |              |             |
| 763-006   | 3 POINT DRIVER AND PASSENGER AND 2 POINT CENTER FRONT SEAT BELT RETRACTORS   |              |             |
| 532-002   | ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN  |              |             |
| 540-067   | 2-SPOKE 18 INCH (450MM) CHERRY WOOD LEATHER WRAPPED  |              |             |
| 765-002   | DRIVER AND PASSENGER INTERIOR SUN VISORS   |              |             |

### Instruments & Controls

|         |   |   |   |
|---------|---|---|---|
| 185-009 | EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS   |   |   |
| 732-047 | FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH DRIVER INSTRUMENT PANEL |   |   |
| 734-047 | FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH CENTER INSTRUMENT PANEL |   |   |
| 870-005 | STAR GAUGES WITH BRIGHT BEZELS                                      |   |   |
| 838-010 | (1) TRACTOR AND (1) TRAILER BRAKE APPLICATION AIR GAUGE             |   |   |
| 840-002 | 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES                    |   |   |
| 198-004 | DASH MOUNTED AIR RESTRICTION GAUGE                                  | 2 |   |
| 721-001 | 97 DB BACKUP ALARM  |   | 3 |
| 149-012 | CRUISE CONTROL SWITCHES IN THE CENTER PANEL                         |   |   |

| Data Code | Description   | Weight Front | Weight Rear |
|-----------|---|--------------|-------------|
| 156-007   | KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY                        |              |             |
| 811-033   | DATASTAR DRIVER DISPLAY IN OVERHEAD CONSOLE AND WARNING LAMP/LIGHT BAR IN DASH NON-DATA LINK                        |              |             |
| 160-038   | HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH  |              |             |
| 844-001   | 2 INCH ELECTRIC FUEL GAUGE  |              |             |
| 845-011   | FUEL FILTER RESTRICTION INDICATOR   |              |             |
| 148-085   | EMISSIONS LIMITED IDLE ADJUST   |              |             |
| 856-001   | ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE   |              |             |
| 854-001   | ENGINE OIL TEMPERATURE GAUGE  |              |             |
| 864-001   | 2 INCH TRANSMISSION OIL TEMPERATURE GAUGE   |              |             |
| 867-016   | OUTSIDE AIR TEMPERATURE GAUGE WITH FAHRENHEIT AND CELSIUS DISPLAY MOUNTED IN OVERHEAD CONSOLE                       |              |             |
| 372-034   | DASH MOUNTED PTO CONTROL WITH INDICATOR LIGHT, GUARD AND PIPING   | 5            |             |
| 49B-998   | NO VEHICLE STABILITY ADVISOR OR CONTROL   |              |             |
| 852-002   | ELECTRIC ENGINE OIL PRESSURE GAUGE  |              |             |
| 1U1-001   | TOP OF DASH NAVIGATION PREP WITH POWER AND GROUND   |              |             |
| 746-116   | AM/FM/WB WORLD TUNER RADIO WITH SIRIUS XM, CD PLAYER, BLUETOOTH, IPOD INTERFACE AND USB AND AUXILIARY INPUTS, J1939 | 10           |             |
| 747-002   | ROOF/OVERHEAD CONSOLE MOUNTED RADIO   |              |             |
| 750-004   | (4) RADIO SPEAKERS IN CAB   |              |             |
| 753-019   | AM/FM ANTENNA MOUNTED ON RH FRONT A-PILLAR  |              |             |
| 748-037   | COBRA 29 LXBT FACTORY INSTALLED CB RADIO WITH WEATHERBAND AND BLUETOOTH   | 5            |             |
| 752-018   | MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNTED ANTENNA SYSTEM   | 4            |             |
| 78C-008   | INTEROPERABLE SDAR ANTENNA, LOCATED FORWARD OF CUSTOMER FURNISHED CAB GUARD   |              |             |
| 810-043   | ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITH ODOMETER  |              |             |
| 812-001   | ELECTRONIC 3000 RPM TACHOMETER  |              |             |
| 813-1B4   | VT-HU CONNECTIVITY PLATFORM HARDWARE  |              |             |

| Data Code | Description  | Weight Front | Weight Rear |
|-----------|--|--------------|-------------|
| 8D1-002   | 2 YEARS DETROIT CONNECT BASE PACKAGE (VIRTUAL TECHNICIAN, DETROIT CONNECT PORTAL ACCESS) FOR VT-HU CONNECTIVITY PLATFORM     |              |             |
| 162-002   | IGNITION SWITCH CONTROLLED ENGINE STOP   |              |             |
| 329-017   | THREE ON/OFF ROCKER SWITCHES IN THE DASH WITH INDICATOR LIGHTS AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT          |              |             |
| 482-001   | BW TRACTOR PROTECTION VALVE  |              |             |
| 883-001   | TRAILER HAND CONTROL BRAKE VALVE   |              |             |
| 842-001   | 2 INCH TURBO AIR PRESSURE GAUGE  |              |             |
| 836-001   | 2 INCH VOLTMETER   |              |             |
| 660-008   | SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY  |              |             |
| 304-018   | CAB MARKER LIGHT AND HEADLIGHT SWITCH WITH SEPARATE SWITCH FOR TRAILER MARKER LIGHTS AND INTERRUPT SWITCH FOR TRAILER MARKER |              |             |
| 882-004   | TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR  |              |             |
| 299-032   | VSM NON CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITHOUT BRAKE OVERRIDE                                    |              |             |
| 298-036   | PACIFIC INSIGHT ELECTRONIC FLASHER   |              |             |

### Design

|         |                        |  |  |
|---------|------------------------|--|--|
| 065-000 | PAINT: ONE SOLID COLOR |  |  |
|---------|------------------------|--|--|

### Color

|         |   |  |  |
|---------|---|--|--|
| 980-8HA | CAB COLOR A: HSB906441 CORAL RED MET PPG BASE/CLEAR   |  |  |
| 96J-001 | CAB INTERIOR PAINTED SAME AS CAB COLOR                |  |  |
| 986-020 | BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT         |  |  |
| 966-998 | PAINT-RR WHEEL COLOR: NONE                            |  |  |
| 963-006 | FENDER, UNDER CAB AND INTERIOR CAB FLOOR UNDERCOATING |  |  |

### Certification / Compliance

|         |   |  |  |
|---------|---|--|--|
| 996-002 | CANADA CMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS |  |  |
| 99A-001 | ENGLISH LANGUAGE MAINTENANCE MANUAL IN EACH TRUCK             |  |  |

### Secondary Factory Options



| Data Code   | Description  | Weight Front | Weight Rear |
|---|--|--------------|-------------|
| 998-032   | CORPORATE PDI CENTER OPTION<br>INSTALLATION/MODIFICATION ONLY  |              |             |
| 95M-998   | NO CUSTOMER FURNISHED MATERIAL<br>SPECIFIED  |              |             |
| 999-014   | DEALER HAS BEEN ADVISED OF AND<br>ACCEPTED RESPONSIBILITY FOR<br>MODIFICATIONS DUE TO POSSIBLE<br>PTO/CHASSIS INTERFERENCE |              |             |
| DLR ADVSD&ACCPTS TRMS OF PIL #395;SPD OF LD VEH LMTD TO 5MPH WHEN LIFT AXLE RSD |  |              |             |

### Raw Performance Data

|         |   |
|---------|---|
| AE4-99D | CALC'D FRAME LENGTH - OVERALL : 368.41                                      |
| AE8-99D | CALCULATED EFFECTIVE BACK OF CAB TO<br>REAR SUSPENSION C/L (CA) : 186.01 in |
| AM6-99D | CALC'D SPACE AVAILABLE FOR DECKPLATE :<br>194.0 in                          |

### Sales Programs

NO SALES PROGRAMS HAVE BEEN SELECTED

## TOTAL VEHICLE SUMMARY

### Weight Summary

|                             | Weight Front | Weight Rear | Total Weight |
|-----------------------------|--------------|-------------|--------------|
| Factory Weight <sup>+</sup> | 13315 lbs    | 9648 lbs    | 22963 lbs    |
| Total Weight <sup>+</sup>   | 13315 lbs    | 9648 lbs    | 22963 lbs    |

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

